

FAIRHURST

DM 1.12.2 CHK'D DATE

P1 PRELIMINARY ISSUE FOR PLANNING REV DESCRIPTION ARCHITECT: THE BUSH CONSULTANCY THIS DRAWING IS COPYRIGHT AND SHALL NOT BE DUPLICATED IN PART OR FULL WITHOUT WRITTEN PERMISSION FROM AMBER MANAGEMENT AND ENGINEERING SERVICES LIMITED. DO NOT SCALE THIS DRAWING, IF IN DOUBT ASK.

NOTES

- 1. ALL EXTERNAL LUMINAIRES TO BE CONTROLLED VIA REMOTE PHOTOCELL.
- 2. ALL BOLLARD LUMINIRES TO BE WIRED WITH WITH XLPE/SWA/LSF ARMOURED CABLING CONTAINED WITHIN 75mm FLEXIDUCT.
- 3. ALL EXTERNAL CABLING AND DUCTS SHALL BE PROVIDED WITH A MINIMUM OF 600mm COVER. WARNING TAPES TO BE PROVIDED OVER TAPES / CABLES.

LUMINAIRE SCHEDULE

- A THORLUX LIGHTING BOLLARD WITH FLEX BASE. BOLLARD TO BE IN PATHWAY MODE.
- AE AS ABOVE BUT COMPLETE WITH 3HR EMERGENCY BACK-UP PACK. TESTING FACILITY TO BE PROVIDED WITHIN EACH BLOCK.
- Z ANSELL LIGHTING VISION 3HP LED 31W BULKHEAD COMPLETE WITH 3HR EMERGENCY BACK-UP PACK.
- A BOLLARD LUMINAIRE.

⊢ Z WALL MOUNTED BULKHEAD.

