

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_w from 1,1 (W/m²K)

Please consult typology, dimensions and glazing

ACCUSTIC INSULATION

Maximum glazing: **45 mm**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207):

Class 4

Water tightness (UNE-EN 12208):

Class 9A

Wind resistance (UNE-EN 12210):

Class A3

Reference test: 2,700 x 2,530 mm. 3 sashes

Security test (PAS 24:2012):

Complies

Reference test: 3 sashes. Configuration 330. 2,701 x 2,517 mm.

SECTIONS	Frame 73 mm Sash 73 mm
PROFILE THICKNESS	Door 1,8 mm
MAXIMUM DIMENSIONS	Width (L) = 1200 mm Height (H) = 3000 mm
MAXIMUM WEIGHT/SASH	120 Kg

Please consult regarding maximum weight and dimensions according to types

FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns
	Wood effect powder coating According to Qualideco standard
	Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25
	Optionally bicoloured

EXTRUSION ALLOY	6063 T-5
POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass: Frame 20 mm Sash 30 mm

OPENING POSIBILITIES	Interior: 1 to 14 sashes Exterior: 1 to 14 sashes Possibility of corner sash at 90° without mullion
ACCESSIBILITY	Possibility of embedded low threshold

