SURFACE LEVEL DATA						Hatched area indicates appr	
NUMBER	MINIMUM LEVEL	MAXIMUM LEVEL	COLOUR	AREA	VOLUME	extents of landfill. Several example are present in this area. Cor	
1	-1.32	-1.00		486.977m2	60.134m3	the contaminated ground as landscaping proposals.	
2	-1.00	-0.50		2968.252m2	728.088m3		
3	-0.50	0.00		17199.486m2	5203.518m3		
4	0.00	0.50		29796.203m2	15478.930m3		
5	0.50	1.00		13061.881m2	4520.730m3		
6	1.00	1.50		3271.823m2	942.911m3	Fill	
7	1.50	2.00		504.189m2	73.173m3		
8	2.00	2.20		19.069m2	1.355m3		
				Dashed of	utline indicates e	xisting building extents	



NOTES © 2020 RPS Group

- 1. This drawing has been prepared in accordance with the scope of RPS's appointment with its client and is subject to the terms and conditions of that appointment. RPS accepts no liability for any use of this document other than by its client and only for the purposes for which it was prepared and provided.
- If received electronically it is the recipients responsibility to print to correct scale. Only written dimensions should be used.
- This drawing should be read in conjunction with all other relevant drawings and specifications.

SCALE 1:500



Design Assumptions

- 1. This drawing is based on Site Vision Surveys Limited Drawing: 0520-ARC-13281 Topographic Survey.
- The Cut and Fill analysis on this drawing is based on 'Proposed Levels' referenced on RPS drawing: 20305B-RPS-00-XX-DR-C-9600.
- 3. The Cut and Fill analysis is based on a general construction depth of: Main Building & Piled Structures = 600mm. MV Intake Buildings & transformer enclosure = 1000mm. Access Roads & Car Park = 450mm. Generators & Fuel Tank Pit = 450mm.
- 4. This analysis assumes that the site is remediated prior to bulk earthworks:a) All existing services removed and backfilled.
- b) Existing hard surfaces removed up to an assumed depth of 300mm and material removed from site.
- c) Topsoil for soft landscaping area's stripped to a depth of
- c) Topsoli for soft landscaping area's stripped to a depin of 300mm excluding area's with existing trees to be retained in accordance with the landscaping proposals.
 d) Existing buildings demolished and concrete foundations and slabs crushed and re-used as part of the bulk earthworks. Volume has been estimated and is to be verified by the contractor on site see note 5 for volume estimates.
- 5. A preliminary 300mm site strip has been used in this analysis. Total Volume = 20,250m³ of which approximately 2,000m³ crushed concrete from demolition works to be retained & re-used as sub-base. Approx. 18,250m³ to be removed
- 6. No bulking factors have been applied to the figures below.
- 7. Dock height taken as 1.25m.
- The Following Volumes have been assumed for arising's from foundations, cable routing and drainage:
- Drainage Attenuation Tanks = 1,600m³ $= 850m^{3}$ = 3,000m³ Ducting Ext. Post Bases & Anti Dig Barriers Foundations = 500m³ = 8,750m³ Crushed Concrete from Demolition Works = 2,000m³ Total = 16 700m³
 - = 16,700m³
- 9. Cut & Fill volumes: = 5,992m³ = 21,017m³
- Earthworks Cut Earthworks Fill Total Cut = 22,692m³ = 21,017m³ Total Fill = 1,675m³ Net (Surplus)

P01 Planning Issue RB JDC 17.02.21 Rev Description By Ckd Date MAKING COMPLEX EASY Sherwood House, Sherwood Avenue, Newark, Nottinghamshire, NG24 1QQ T:01636 605 700 E: rpsnewark@rpsgroup.com Client Project Bracknell Data Centre Grading Cut & Fill Title Date Created RPS Project Number Scale @ A0 17.02.2021 NK020305B 1:750 Task Team Information Task Information Manager Author Manager MRH MH JDC Status S1 (Suitable for Information) Document Number Revision 20305B-RPS-00-XX-DR-C-9620 P01 Project Code - Originator - Zone - Level - Type - Role - Drawing Number rpsgroup.com