



- Notes:**
1. Standard scaffold poles.
  2. Heavy gauge 2m tall galvanised tube and welded mesh infill panels.
  3. Panels secured to uprights and cross-members with wire ties.
  4. Ground level.
  5. Uprights driven into the ground secure (minimum depth 0.6m).
  6. Tree Protection as per British Standards 5837:2012 - Trees in relation to design, demolition and construction.

Note: Please do not scale from this drawing

**IronsideFarrar**  
Environmental Consultants

EDINBURGH | GLASGOW | MANCHESTER

---

Project Name  
**Halbeath Landscape Support Services**

Client  
**Shepherd Offshore**

---

Title  
**Tree Removals & Protection Plan**

---

N. Point

Scale  
**1:1250**

Bar Scale  
0 25 50m  
1:1250

---

Date  
**31.03.21**

Drawn by  
**GB**

Status  
**GB**

Paper Size  
**A1**

Checked by  
**GS**

Project No  
**50404-602**

Quality Assurance  
ISO 9001:2015  
SIS UKAS Certificate GB0254539

Copyright Acknowledgement  
© Ironside Farrar Environmental Consultants 2020  
All rights reserved. Licence No. AL100017966

**FOR INFORMATION**

Drawing No  
**50404-602**

Revision  
**P02**