

Specifications

TSX Pressure Washer

| Technical specifications | | | | |
|---|------------------|-----------------------|-----------------------|-----------------------|
| | | HDS 6/10 | HDS 6/12 | HDS 6/14 |
| Main Supply | | | | |
| Voltage | V | 100 | 230-240 | 230 |
| Current type | Hz | 1~ 50 | 1~ 50 | 1~ 50 |
| Connected load | kW | 2,9 | 3,0 | 3,6 |
| Protection (slow) | A | 30 | 13 | 16 |
| Type of protection | -- | IPX5 | IPX5 | IPX5 |
| Protective class | -- | I | I | I |
| Maximum allowed net impedance | Ohm | 0.3710 | 0.3710 | 0.3710 |
| Water connection | | | | |
| Max. feed temperature | °C | 30 | 30 | 30 |
| Min. feed volume | l/h (l/min) | 800 (13,3) | 800 (13,3) | 800 (13,3) |
| Suck height from open container (20 °C) | m | 0,5 | 0,5 | 0,5 |
| Max. feed pressure | MPa (bar) | 1 (10) | 1 (10) | 1 (10) |
| Performance data | | | | |
| Water flow rate | l/h (l/min) | 240-560 (4-9,3) | 240-560 (4-9,3) | 240-560 (4-9,3) |
| Operating pressure of water (using standard nozzle) | MPa (bar) | 3-10 (30-100) | 3-12 (30-120) | 3-14 (30-140) |
| Max. excess operating pressure (safety valve) | MPa (bar) | 12 (120) | 15 (150) | 17 (170) |
| Steam flow rate | l/h (l/min) | 240-290 (4-4,8) | 240-290 (4-4,8) | 240-290 (4-4,8) |
| Max. operating pressure for working with steam (using steam nozzle) | MPa (bar) | 3,2 (32) | 3,2 (32) | 3,2 (32) |
| Part no. of steam nozzle | -- | 5.130-453.0 | 5.130-453.0 | 5.130-453.0 |
| Max. operating temperature of hot water | °C | 98 | 98 | 98 |
| Working temperature steam operation | °C | 155 | 155 | 155 |
| Detergent suck in | l/h (l/min) | 0-33,6 (0-0,56) | 0-33,6 (0-0,56) | 0-33,6 (0-0,56) |
| Burner performance | kW | 43 | 43 | 43 |
| Maximum consumption of heating oil | kg/h | 3,5 | 3,5 | 3,5 |
| Max. recoil force of trigger gun | N | 21,8 | 25,6 | 25,6 |
| Nozzle size | -- | 043 | 042 | 036 |
| Values determined as per EN 60355-2-79 | | | | |
| Noise emission | | | | |
| Sound pressure level L_{pA} | dB(A) | 76 | 76 | 76 |
| Uncertainty K_{pA} | dB(A) | 3 | 3 | 3 |
| Sound power level L_{WA} + Uncertainty K_{WA} | dB(A) | 94 | 94 | 94 |
| Hand-arm vibration value | | | | |
| Hand spray gun | m/s ² | 2,7 | 2,7 | 2,7 |
| Spray lance | m/s ² | 5,4 | 5,4 | 5,4 |
| Uncertainty K | m/s ² | 0,3 | 0,3 | 0,3 |
| Fuel | | | | |
| Fuel | -- | Fuel oil EL or Diesel | Fuel oil EL or Diesel | Fuel oil EL or Diesel |
| Amount of oil | l | 0,3 | 0,3 | 0,3 |
| Oil grade | -- | 0W40 | 0W40 | 0W40 |
| Dimensions and weights | | | | |
| Length x width x height | mm | 1060 x 650 x 920 | 1060 x 650 x 920 | 1060 x 650 x 920 |
| Typical operating weight, C | kg | 108,1 | 108,1 | 108,1 |
| Typical operating weight, CX | kg | 111 | 111 | 111 |
| Fuel tank | l | 15,5 | 15,5 | 15,5 |
| Detergent Tank | l | 15,5 | 15,5 | 15,5 |

WD4 Vacuum

Technical specifications

| | | |
|--|-------------------|-------|
| Voltage 1~50-60 Hz | 220 - 240 | V |
| Output P _{nom} | 1000 | W |
| Mains fuse (slow-blow) | 13 | A |
| Container capacity | 20 | l |
| Water intake with handle | 12 | l |
| Water intake with floor nozzle | 10 | l |
| Power cord | H05VV-F 2x0,75 | |
| Sound pressure level (EN 60704-2-1) | 72 | dB(A) |
| Weight (without acces- sories) | 7,6 | kg |

Subject to technical modifications!