



THIS DRAWING IS THE PROPERTY OF OBG LTD. COPYRIGHT IS RESERVED BY THEM AND THE DRAWING IS ISSUED ON THE CONDITION THAT IT IS NOT COPIED, REPRODUCED, RETAINED, OR DISCLOSED TO ANY UNAUTHORIZED PERSON, EITHER WHOLLY OR IN PART WITHOUT THE CONSENT IN WRITING OF OBG LTD.

N.B. ANY VARIATIONS BETWEEN STATED DIMENSIONS AND SITE DIMENSIONS SHOULD BE REPORTED TO THE SURVEYOR PRIOR TO WORK BEING CARRIED OUT


Proposed West Elevation
Scale 1:50



Proposed East Elevation
Scale 1:50





Proposed South Elevation
Scale 1:50



Proposed Floor Electrics & Roof Plan
Scale 1:50


ELECTRICS	
ELECTRICAL LEGEND	
	RADIATOR (TRV)
	Low Energy Spotlight
	EXTERNAL/WALL MOUNTED LIGHT
	SMOKE DETECTOR
	MECHANICAL EXTRACTOR FAN (Up To 60 l/s)
	2/13 AMP (HIGH LEVEL)
	2/13 AMP (LOW LEVEL)
	LIGHT SWITCH
	T.V. POINT
	COOKER POINT
	ETHERNET POINT
	CONSUMER UNIT



Vertical boards will be fixed to horizontal battens and if the boards are tight-jointed it will be necessary to introduce vertical counter battens behind these horizontal battens which would otherwise prevent drainage and vertical circulation of air, see Figure 2. Although a 12mm minimum gap would theoretically be adequate between the horizontal battens and the inner wall, counter battens of solid wood should be increased in thickness to reduce the risk of the wood splitting when the battens are nailed through to studwork or masonry behind. If the horizontal battens are only to be fixed to the counter battens, these must be of sufficient thickness to take the fixing nails. If the horizontal battens are unsupported other than at studs or counter battens they should also be stiff enough not to flex unduly when the boards are nailed to them.

Figure 2 Typical construction: vertical tongued and grooved boarding on horizontal battens and counterbattens.

Proposed Location Plan
Scale 1:500



TYPICAL OPENING IN EXTERNAL KIT LINTEL ARRANGEMENT

Location	Nailing Details
01. Flooring dwangs.	2 no. 100x4.5mm galvanised round wire nails to each end - one end face nailed one end skew nailed.
02. Plasterboard dwangs.	2 no. 100x4.5mm galvanised round wire nails to each end - one end face nailed one end skew nailed.
03. Chipboard flooring.	65x3.35mm sheradized annular ring shank nails @ 150mm centres along perpendicular joist.
04. Joist hangers.	30mm sheradized square twist nails to all holes.

Section 1 - Floor Joist Erection

- Location**
01. Wall plate to brickwork.
 02. Floor joists to wallplate/headbinder.
 03. Header joist/floor joist junction.
 04. Header joists to wallplate/headbinder.
 05. Full depth dwangs (strutting/support)
 06. Perimeter plate to joist.
 07. Cam plate to joist.

Nailing Detail

- Spike into mortar joints with 1 no. 100mm x 4.5mm galvanised round wire nails @ 600mm centres.
- Skew nailed with 2 no. 100x4.5mm galvanised round wire nails.
- Face nailed with 2 no. 100x4.5 galvanised round wire nails.
- Skew nailed with 2 no. 100x4.5mm galvanised round wire nails @ 400mm centres.
- Face skew nailed with 2 no. 100x4.5mm galvanised round wire nails.
- Face nailed with 2 no. 100x4.5mm galvanised round wire nails @ 300mm centres.
- Face nailed with 3 no. 30mm sheradized square twist nails to each joist.

Section 2 - Wall Panel Erection

- Location**
01. Wall panel bottom rail to joists.
 02. Wall panel to wall panel.
 03. Head binder to wall panel.
 04. Cavity barrier to panels.
 05. Restraint straps.

Nailing detail

- 100x4.5mm galvanised round wire nails @ 300mm centres.
- 2 no. 100x4.5mm galvanised round wire nails @ 450mm centres angled alternately from each side.
- 100x4.5mm galvanised round wire nails @ 600mm centres.
- 65x3.35mm sheradized annular ring shank nails - 2 rows of 4 @ 100mm centres. Staggered.

Section 3 - Roof Erection

- Location**
01. Roof trusses.
 02. Spandrel panel to headbinder.
 03. Spandrel panel to spandrel panel.
 04. Truss bracing.
 05. Gable ladder to end truss.
 06. Gable ladder to spandrel.
 07. Fascia Board.
 08. Timber sarking.
 09. Plywood sarking.
 10. BS7471F felt under counter batten.
 11. Tile Battens.
 12. Cistern spreader beams on ceiling tie.
 13. Cistern bearer to cistern bearer.
 14. Chipboard to cistern bearers.


Nailing Detail

- 30mm sheradized square twist nails to all holes of truss clip.
- 100x4.5mm galvanised round wire nails @ 300 centres.
- 100x4.5mm galvanised round wire nails to top of truss ceiling tie at node points.
- 2 no. 100x4.5mm galvanised round wire nails to top of truss ceiling tie at node points.
- 2 no. 100x4.5mm galvanised round wire nails @ 600centres.
- 2 no. 100x4.5mm galvanised round wire nails at each member.
- 3 no. 65x3.35mm sheradized annular ring shank nails to end of each truss.
- 3 no. 65x3.35mm sheradized annular ring shank nails to end of each truss.
- 40x2.65mm galvanised clout nails @ 200mm centres.
- 40x2.65mm galvanised clout nails @ 200mm centres.
- 1 no. 65x3.35 sheradized annular ring shank nail to each truss.
- 2 no. 100x4.5mm galvanised round wire nails skew nailed to each tie.
- 2 no. 100x4.5mm galvanised round wire nails skew nailed.
- 65x3.35 sheradized annular ring shank nails @ 150mm centres.

Window Fixings

- Windows fixed at 300c/c with 120x30x2 stainless steel clips onto window bracket each double screwed with 2 no. 4.2mm Ø screws.

Proposed Location Plan Unavailable
MAPPING SYSTEM DOWN
(TO BE UPDATED)



Ref	Date	Revision	By
A	12.05.2021	As per meeting	SD
	29.04.2021	First Issue	SD
Client: Muhammed Chaudhry 29 Silvergrove St Glasgow G40 1DE			
Project: Caden Garden Room			
Title: Job No. 1496 - Muhammed Chaudhry			
Drawing No:	Rev:	Scale:	
01		VAR	
Date:	Drawn by:	Checked by:	
16/03/21	DF	DF	

272 LANGMUIR ROAD, GLASGOW, G69 7RR
T: 0141 896 0272
E mail: david@outdoorbuildinggroup.co.uk
Web: www.outdoorbuildinggroup.co.uk