

SCALE BAR. 1:50



BOUNDARY.

BOUNDARY.

ACCESS.

APEX

STOCK STORAGE.

W/C.

INTERNAL WALL WITHIN STOCK/STORE
TO BE CONSTRUCTED FROM 100MM LIGHTWEIGHT
BLOCKS WITH 12MM PLASTER AND 3MM SKIM FINISH.
MINIMUM MASS TO BE 90KG/M2 IN ACCORDANCE
WITH BUILDING REGULATIONS PART 'E'.

EXTENAL WALLS TO BE 100MM LIGHTWEIGHT BLOCK INNER LEAF WITH
100MM CAVITY AND 100MM BRICK OUTER SKIN. INCLUDE 100MM KINGSPAN
THERMAL INSULATION WITHIN CAVITY TO GIVE A 'U' VALUE OF 0.28W/M2K.
INSTALL STAINLESS STEEL WALL TIES AT 750MM CENTERS HORIZONTALLY AND 450MM
VERTICALLY. (AROUND STRUCTURAL OPENINGS 225MM CENTERS AND INSTALL CAVITY
CLOSERS.) INTERNAL FACES TO HAVE 12MM PLASTER AND SKIM FINISH .
ALL LINTELS TO HAVE MINIMUM 150MM LOADBEARING ONTO MASONRY EITHER END.

P & ER
DEVELOPMENT CONTROL
REC'D 1- JUN 2021

PLANMAN

BUILDING DESIGN SERVICES.

No 10 MILTON STREET, GOOLE, EAST YORKSHIRE. DN14 6EL.
TEL; 07901 792867. E-MAIL; planman50@yahoo.co.uk.

CLIENT: MR SELVAN JAYARAMA.

DWG No; MC2A

PROJECT; PROPOSED ALTERATIONS.
PROPOSED STOCK/STORE FLOOR PLAN.

DATE: 20.05.21

SCALE: 1:50