

PRODUCT NAME				RXYSCQ-TV1	RXYSCQ5TMV1B	
Recommended combinatio					4 x FXSQ32A2VEB	
Cooling capacity	Prated,c		kW		14.0 (1)	
Heating capacity	Prated,h		kW		9.7	
SCOP					4.7	
SEER					7.7	
Space cooling	A Condition (35°C	EERd			2.7	
		Pdc	kW		14.0	
	B Condition (30°C	EERd				5.0
		Pdc	kW			10.3
	C Condition (25°C	EERd				10.5
		Pdc	kW			6.6
	D Condition (20°C	EERd				19.9
		Pdc	kW			4.9
Space heating (Average clin TBivalent	TOL	COPd (declared C			2.7	
		Pdh (declared he kW			9.7	
		Tbiv (bivalent ter °C				-10
		COPd (declared C				2.7
	A Condition (-7°C	Pdh (declared he kW				9.7
		Tol (temperature °C				-10
	B Condition (2°C	COPd (declared C				3.1
		Pdh (declared he kW				8.5
	C Condition (7°C	COPd (declared C				4.5
		Pdh (declared he kW				5.2
	D Condition (12°C	COPd (declared C				6.4
		Pdh (declared he kW				3.4
		COPd (declared C				8.1
		Pdh (declared he kW				4.0
	Capacity range	HP				5
	Maximum number of conn					64 (6)
Indoor index connection	Min.				62.5	
	Max.				162.5	
Dimensions	Unit	Height	Mm		823	
		Width	Mm		940	
		Depth	Mm		460	
Weight	Unit		kg		89	
Compressor	Type				Hermetically sealed swing compressor	
Operation range	Cooling	Min.	°CDB		-5.0	
		Max.	°CDB		46.0	
	Heating	Min.	°CWB			-20.0
		Max.	°CWB			15.5
Sound power level	Cooling	Nom.	dBa		69.0 (7)	
Sound pressure level	Cooling	Nom.	dBa		52.0 (8)	
Refrigerant	Type				R-410A	
	GWP				2,087.5	
	Charge		kg		3.7	
	Charge		TCO2Eq		7.7	
Piping connections	Liquid	Type			Flare connection	
		OD	Mm		9.52	
	Gas	Type				Flare connection
		OD	Mm			15.9
Total piping lengtl System	Actual	m			300 (9)	

Standard Accessories	Installation manu.		1
	Operation manua		1
	Connection pipes		1
Power supply	Name		V1
	Phase		1~
	Frequency	Hz	50
	Voltage	V	220-240