



RAMP NOTES

RAMP DESCRIPTION

ALL METALWORK TO BE GALVANISED PRIOR TO INSTALLAION. NEW GALVANISED RAMP PLATFORM TO BE BUILT OVER EXISTING ENTRANCE STEP. ENSURE PLATFORM IS LEVEL WITH THRESHOLD ENSURE ALL EDGES OF RAMP HAVE 100MM UPSTANDS.

FOUNDATIONS

PAD FOUNDATIONS TO BE 300 X 300 X 150MM QUICK-SETTING CONCRETE AND PRIOR TO POURING, THE TOP OF EACH PAD MUST BE AT A DEPTH OF 450MM BELOW GROUND LEVEL AND BACKFILLED WITH TYPE ONE HARDCORE. THE PAD WILL NOT BEAR ON SOFT SPOTS OR ON GROUND WITH ALLOWABLE GROUND BEARING PRESSURE OF LESS THAN 40KN/M².

FIXING

EACH POST BASE PLATE TO BE FIXED TO EXISTING SLABS OR PAD FOUNDATIONS USING M8 X 75MM RAWL BOLTS.

DRAWING STATUS

PLANNING & WARRANT



DESIGN SERVICES
350 Darnick Street
GLASGOW
G21 4BA
Tel 0141 287 2200
Fax 0141 287 1969

JOB

**PROPOSED RAMP @
10 VICTORY WAY**

TITLE

EXISTING PLAN

SCALE @ A3

SCALE 1:50

JOB NO.

02

DRG NO.

02

DATE

AUG 2021

APPROVED

..

REVISION

-

DRAWN

DPM