



SIDE ELEVATION (NORTH/EAST)

REAR ELEVATION (NORTH/WEST)

SCALE 1:100

10 metres

NOTES

EXTERNAL FINISHES

FOR DETAILS OF EXTERNAL FINISHES SEE DRAWING No $8536 \ / \ 596$

- CAVITY VENTILATION TO BE PROVIDED BY RYTON SLIMVENT OR SIMILAR CAVITY PERPEND VENTS TO BE POSITIONED AT 1200mm MAXIMUM CENTRES IN THE EXTERNAL CLADDING AS INDICATED BELOW.
 - a. IN THE BASECOURSE BELOW INNER LEAF DPC LEVEL.
 - AT THE TOP OF THE WALL BETWEEN THE LEVEL OF THE UNDERSIDE OF LINTELS AND THE HORIZONTAL CAVITY BARRIER AT SOFFIT LEVEL.
 - c. AT GABLES (AS a) AND FOLLOWING THE LINE OF THE VERGE AT WALLHEAD LEVEL.
 - d. AT HIGH AND LOW LEVEL ON EACH SIDE OF ANY MOVEMENT JOINT OR FULL HEIGHT CAVITY BARRIER.
- 3. PROVIDE A WEEP VENT AT EACH END OF BIRTLEY LINTELS, AT A MAXIMUM OF 450mm CTS ABOVE WINDOW & DOOR OPENINGS AND AT BOTTOM OF CAVITY TRAYS WHERE APPLICABLE.

