



Our chips are painted in Ecopro Silicate Masonry Paint, but to be sure it's the perfect colour for you, test with one of our handy 100ml sample pots

Earthborn

Earthborn is a family owned company based in Cheshire. It was established in 2002 by John Dison who identified the need for a range of paints that were less harmful to the environment, healthier to use and better for the fabric of the building.

Earthborn Ecopro Silicate Masonry Paint is available in 48 beautiful shades and dries to a classic matt finish. Used with Ecopro Silicate Primer, it creates a permanent chemical bond with mineral substrates resulting in an extremely long service life.

The silicate based system is highly breathable yet water resistant. It is also hardwearing and a user friendly alternative to traditional lime based and conventional coatings, making it especially suitable for use on historic buildings and listed properties.



info@earthbornpaints.co.uk

earthborn®

www.earthbornpaints.co.uk

Silicate Masonry System

Where to use

A long lasting, highly breathable finish suitable for lime render, it can be used on many interior and exterior mineral surfaces e.g. brick, stone, cement, concrete, pebble dash and plaster, along with sound silicate-based paint surfaces.

Preparation

First, remove any loose or flaking material and ensure that all surfaces are clean, dry, sound and algae free. Take care to mask all adjacent glass, metal and ceramic before use.

Step 1

Apply a coat of Ecopro Silicate Primer.

Step 2

Apply a coat of Ecopro Silicate Masonry Paint, diluted with 20% Ecopro Silicate Primer.

Step 3

Apply a final coat of Ecopro Silicate Masonry Paint.

Coverage

Paint and Primer
5-7m² per litre

Tin Sizes

Paint and Primer
100ml, 5L & 10L

Notes

Previous paint coatings, apart from a sound silicate paint system, must be removed before applying Earthborn Ecopro Silicate Masonry System. It should not be applied over conventional 'plastic' masonry paint.

Do not use if the working temperature is below 8°C or expected to fall below 8°C within 24 hours of application.

New lime render must be allowed to fully cure before painting.

Moisture content in wall must not be higher than 20% at time of application.

earthborn
ECOPRO

SILICATE MASONRY
PAINT