Water Use Analysis

Penoffa Farm Treatment Plant and Drainage Field

26 November 2021

NIDUS ARCHITECTS

Little Folly, Mutton Dingle, LD8 2TL T:01544 350550 E: <u>hello@nidusarchitects.co.uk</u>

Rev -

CONTENTS

Introduction	3
Section 1: Foul Water Management	4
Section 2: Surface Water Management	11

Introduction

This document provides information relevant to water management from the proposed development of Penoffa Farm.

This application accompanies an application (21/1801/FUL) to convert an existing cow shed into an event space for wedding, corporate and community events. The cow shed is highlighted on the plan below.



This document demonstrates that the proposed use will dramatically decrease the amount of waste water currently produced by the site.

The proposed scheme enables a reduction in daily waste water of approximately 736 litres per day. This is demonstrated in **Section 1: Foul Water Management**.

It should be noted that the calculation of water usage by the New Development in **Section 1** uses water efficient fixtures and fittings. Collection of grey water for wc flushing is also proposed and provides approximately 15 l/person/day.

Surface Water Management,

Surface water produced by the development is addressed as part of application 21/1801/FUL

SECTION 1: FOUL WATER MANAGEMENT

Existing Development

Tables 1 shows a conservative estimate of water use per week for the barn under its existing use as a cow shed. The barn needs to be cleaned approximately once daily, although this was sometimes more frequent, additional water troughs required cleaning out at least once per day. Cleaning of the barn was undertaken with a commercial grade pressure washer using 9.33 litres of water per minute. The barn is approximately 688m2 and operated for around 2hrs per day.

It should be noted that the calculation does not account for cleaning of the yard area which was undertaken between 2 and 4 times per week depending on the time of year, neither does it account for cleaning of machinery associated with farm use.

The daily use consumption is calculated only on those items undertaken on a daily basis, the weekly total is therefore based on 7 days.

Table 1

LARGE COW SHED: EXISTING USE		(1)	(2)	(3)	(4)
Installation Type	Unit of measure	Capacity/ flow rate	Use factor	Fixed use (litres/day)	Litres/day = [(1) x (2) + (3)
Washing down barn	pressure water (litres/m)	9.33	120	0.00	1119.6
Water Troughs	volume per trough	180	10	0.00	1800
	(5)	Total calculated use = (Sum column 4)		2919.6	
	(6)	Contribution from grey water (litres/day)			0
	(7)	Contribution from rainwater (litres/day)			0
	(8)	Total water consumption = [(5) - (6) - (7)]			2919.6
	(9)	External water use			0
	(10)	Total water consumption = (8) + (9) (litres/day)		2919.6	
		TOTAL COMBINED DAILY USE:		<u>2919.6</u>	
		TOTAL COMB	INED WEEKLY	USE:	20437.2

Summary

Even using conservative calculations the existing development has high level of water use, furthermore waste water washed into the drainage system is likely to contain high levels of animal waste, contributing to high phosphate levels.

• 20,437 litres/week of waste water from the site

Proposed Development

Tables 2 and 3 and 4 show the water use per week for the proposed use as an event space.

Due to set up and clearance it is anticipated that the event space has a maximum potential to be used 3 days per week at full capacity. Table 2 demonstrates the potential water use for a week if the event barn achieved maximum capacity across all 3 days. The calculations include associated staff use during this period.

Table 2

PROPOSED EVENT BARN: GUESTS		(1)	(2)	(3)	(4)
Installation Type	Unit of measure	Capacity/ flow rate	Use factor	Fixed use (litres/ person/day)	Litres/person/day = [(1) x (2) + (3)
WC (single flush)	Flush volume (litres)	0	4.42	0.00	0
WC (duel flush)	Full flush volume (litres)	0	1.46	0.00	0
	Part flush volume (litres)	4	2.96	0.00	11.84
WC (multiple fittings)	Average effective flushing volume (litres)		4.42	0.00	0
Taps (excluding kitchen/utility room taps)	Flow rate (litres/minute)	7.6	0	1.58	1.58
Bath (where shower also present)	Capacity to overflow (litres)	0	0.11	0.00	0
Shower (where bath also present)	Flow rate (litres/minute)	0	4.37	0.00	0
Bath only	Capacity to overflow (litres)	0	0.50	0.00	0
Shower only	Flow rate (litres/minute)	0	5.60	0.00	0
Kitchen/utility room sink taps	Flow rate (litres/minute)	0	0.44	0.00	0
Washing machine (water efficient model)	Litres/kg dry load	0	2.1	0.00	0
Dishwasher (water efficient model)	Litres/place setting	0	3.6	0.00	0
Waste disposal unit	Litres/use	0	3.08	0.00	0
Water softener	Litres/person/day	0	1.0	0.00	0
	(5)	Total calculated use = (Sum column 4)		13.42	
	(6)	Contribution from grey water (litres/person/day)		5	
	(7)	Contribution from rainwater (litres/person/day)		0	
	(8)	Normalisation factor		0.91	
	(9)	Total water consumption = [(5) - (6) - (7) × (8)]		8.42	
	(10)	External water use		0	
	(11)	Total water consumption = (9) + (10) (litres/person/day)		8.42	
		Max. No of people			120
		TOTAL COMBINED DAILY USE:		<u>1010.4</u>	
		TOTAL COMBINED WEEKLY USE:			<u>3031.2</u>

Table 3 demonstrates water use for the supporting camping facilities. Camping would be provided only for people using the event space, with the use of existing site facilities and acknowledging that not all guests will camp the calculations allow for 65 guests. Showering facilities would be provided within the event space and the calculation is based upon people staying at the campsite using these facilities. It should be noted that use of other facilities, such as toilets and washbasins are incorporated in the Table 2 calculation.

Table 3

PROPOSED EVENT BARN: CAMPING		(1)	(2)	(3)	(4)
Installation Type	Unit of measure	Capacity/ flow rate	Use factor	Fixed use (litres/ person/day)	Litres/person/day = [(1) x (2) + (3)
WC (single flush)	Flush volume (litres)	0	4.42	0.00	0
WC (duel flush)	Full flush volume (litres)	0	1.46	0.00	0
	Part flush volume (litres)	0	2.96	0.00	0
WC (multiple fittings)	Average effective flushing volume (litres)		4.42	0.00	0
Taps (excluding kitchen/utility room taps)	Flow rate (litres/minute)	0	1.58	1.58	1.58
Bath (where shower also present)	Capacity to overflow (litres)	0	0.11	0.00	0
Shower (where bath also present)	Flow rate (litres/minute)	0	5.60	0.00	0
Bath only	Capacity to overflow (litres)	0	0.50	0.00	0
Shower only	Flow rate (litres/minute)	7.6	5.60	0.00	42.56
Kitchen/utility room sink taps	Flow rate (litres/minute)	0	0.44	0.00	0
Washing machine (water efficient model)	Litres/kg dry load	0	2.1	0.00	0
Dishwasher (water efficient model)	Litres/place setting	0	3.6	0.00	0
Waste disposal unit	Litres/use	0	3.08	0.00	0
Water softener	Litres/person/day	0	1.0	0.00	0
	(5)	Total calculated use = (Sum column 4)		44.14	
	(6)	Contribution from grey water (litres/person/day)		10	
	(7)	Contribution from rainwater (litres/person/day)		0	
	(8)	Normalisation factor		0.91	
	(9)	Total water consumption = [(5) - (6) - (7) × (8)]		34.14	
	(10)	External water use		0	
	(11)	Total water consumption = (9) + (10) (litres/person/day)		34.14	
		Max. No of people		65	
		TOTAL COMBINED DAILY USE:		<u>2219.1</u>	
		TOTAL COMBINED WEEKLY USE:			<u>6657.3</u>

Table 4 demonstrates water use of the bar and kitchen facilities when the event space is running at full capacity.

Table 4

PROPOSED EVENT BARN: BAR AND KITCHEN		(1)	(2)	(3)	(4)
Installation Type	Unit of measure	Capacity/ flow rate	Use factor	Fixed use (litres/ person/day)	Litres/person/day = [(1) x (2) + (3)
WC (single flush)	Flush volume (litres)	0	4.42	0.00	0
WC (duel flush)	Full flush volume (litres)	0	1.46	0.00	0
	Part flush volume (litres)	0	2.96	0.00	0
WC (multiple fittings)	Average effective flushing volume (litres)		4.42	0.00	0
Taps (excluding kitchen/utility room taps)	Flow rate (litres/minute)	0	0	0.00	0
Bath (where shower also present)	Capacity to overflow (litres)	0	0.11	0.00	0
Shower (where bath also present)	Flow rate (litres/minute)	0	4.37	0.00	0
Bath only	Capacity to overflow (litres)	0	0.50	0.00	0
Shower only	Flow rate (litres/minute)	0	5.60	0.00	0
Kitchen/utility room sink taps	Flow rate (litres/minute)	12	0.1	0.00	1.2
Washing machine (water efficient model)	Litres/kg dry load	0	2.1	0.00	0
Dishwasher (water efficient model)	Litres/place setting	1.08	3.6	0.00	3.888
Waste disposal unit	Litres/use	1	3.08	0.00	3.08
Water softener	Litres/person/day	0	1.0	0.00	0
	(5)	Total calculated use = (Sum column 4)		8.168	
	(6)	Contribution from grey water (litres/person/day)			0
	(7)	Contribution from rainwater (litres/person/day)			0
	(8)	Normalisation factor			0.91
	(9)	Total water consumption = [(5) - (6) - (7) x (8)]		8.168	
	(10)	External water use		0	
	(11)	Total water consumption = (9) + (10) (litres/person/day)		8.168	
		Max. No of people			120
		TOTAL COMBINED DAILY USE:			<u>980.16</u>
		TOTAL COMBINED WEEKLY USE:			<u>6861.12</u>

Summary

The proposed development will feature modern, water efficient appliances, additionally a grey water storage system will have the potential to provide unto 20 litres of grey water per person per day. Through the above an overall use of;

- 3,031 litres/week will be used by event space guests
- 6,657 litres/week will be used by people camping
- 6,860 litres/week will be used by the kitchen and bar facilities
- TOTAL litres/week = 16,548

Conclusion

Existing Development:	20,437 l/week
Proposed Development:	16,548 l/week

A reduction in waste water of approximately **3,889 litres/week** or **555 litres/day** will be achieved by the event space replacing the existing cow shed.