Elevation view from outside



NOTE

Use figured dimensions only. Scale drawing only when a scale bar is present. All dimensions to be checked by user and any discrepancies, error or omissions to be reported to the architect before work commences. Read this drawing with all relevant protections.

General notes

- 1. Windows to be glazed with clear Timbalite 4/6/4 or 4/4/4 low E krypton filled double glazed units with black spacer bars.
- Glazing units can be putty faced and timber beaded.
- 2. Glazing units within 800mm of finished floor level to be toughened safety glass to BS.6206.1981 & restrict fitted as required.
- 3. All timber to be Accoya/Hardwood (window units and frame).
- 4. All windows to be fully weather stripped with schlegel aquamac soft compression seals.
- 5. Windows to be fitted with lead counter balance weights.
- 6. Ironmongery to include 4 x bearing type sash pulleys 2 x sash lifts 1 x fitch catch; colour/finish polished chrome
- 7. Security Provide 2 no security sash stop locks to each set of opening sashes.
- 8. Paint finish: white factory spray applied microporous paint.

Rev Date Drn Chkd Description

CONSTRUCTION ISSUE

client:

Commercial Development Projects

104-106 High Street, Sevenoaks

drawing title: Window Details 3

Window Details 3
Horn Details

1:2 Jan 2022 GG AT

drowing number: revisit

1524-PL-1452 --

1524-PL-1452



Compton House, Walnut Tree Close, Guildford, Surrey, GU1 4TX [t] 01483 455100 [f] 01483 455210 [E] design@accordarchitecture.com