SOFT DETAILED LANDSCAPE PROPOSAL FOR PLOTS

1.2 All planting beds shall be a minimum of 1 metre wide, path edgings, ensure that the bed has space free from concrete footings before planting. If the bed is sealed with concrete, then the landscape contractor shall contact the site manager or landscape architect to determine if is not as drawn, the contractor shall re- cultivate them to

spraying aparatus, an approved translocated systemic herbicide to the manufacturer's instructions and to 1997 following cultivation, to allow dormant seed to germinate.

All spraying shall be carried out by skilled and qualified

site to ensure it Conforms to BS 3882:2015, being free from rocks larger than 50m diameter, concrete, all roots, wire, brick, and have less than 20% clay. Allow for pre-application of herbicide as above. Fertilise with 100g over thoroughly or machine rotovate soil to a depth of

adjacent paved surfaces, to receive rain water run off. The landscape contractor is responsible for ensuring that the developer and/or main contractor have failed to supply and spread topsoil to the recessed level. The landscape

is paving adjacent to it topsoil levels of the grass areas shall be graded to finish flush with the finished pavement level to allow surface water to drain from pavements to soft areas. Soil of grass areas should therefore never be

diameter), concrete, roots, wire and brick, and have less than greater than 20% clay. Such soil shall be cultivated as set out above. Representative samples shall first be

pots are 19cm diameter and 15cm deep, 5L pots are 22.5cm diameter and 18cm deep, 10L pots are 28cm and 30cm deep, 2SL pots are 38.5cm diameter and 35cm deep, 30L pots are 41cm diameter and 36cm deep, 40L pots are 50cm diameter and 45cm deep, 50L pots are checked on site to ensure compliance with those specified. Pots will be rejected if shrubs are supplied of a size which are not fully grown into the pot e.g. a 9cm plant recently potted into a 3L container. All shrubs, shall Specification standards for each species and pot size will be rejected. Plant stock shall be bushy, healthy, disease free, not pot bound, leggy or spindly. There should be a minimum of 5 breaks per shrub. This specification is the this standard in the sole opinion of the inspecting

0.6m for corners or where space is restricted). Include for adapting any panels for locations where walls or fence: are lower than 1.8m. Fix trellis panels to the walls/ fence: using non rusting screws 125mm long (to be approved that the panel is mounted sufficiently far from the wall/ fence to allow twining of stems. Ensure that all timber is and then painted with a dark brown non phyto-toxic