


PLAN





07716 825217 oscar@foxframing.co.uk

PLEASE NOTE:

FOUNDATION SPEC

TO BE CONFIRMED BY GROUND WORKS CONTRACTOR OR STRUCTURAL ENGINEER

BRICKWORK SPEC:

300MM HIGH (4 COURSES)

TWIN SKIN 225MM WIDE

PLEASE NOTE: BRICKWORK NEEDS TO SIT ON TOP OF THE FINISHED CONCRETE SLAB

FRAME INFORMATION:

7.5M WIDE x 6M DEEP TWO BAY FULL HEIGHT FRAME
300 X 200MM FRONT ELEVATION POSTS
200 X 200MM FRONT EAVES BEAM
200 X 200MM REAR ELEVATION POSTS/BEAMS
150 x 150MM TIE BEAM SUPPORT POSTS/BEAMS
CLEARANCE UNDER THE MAIN BEAM TO BE 2.6M
45 DEGREE GABLE ENDED ROOF
EXTERNAL STAIRS

ROOF RAFTERS & STUDWORK TO BE POSITIONED @ 400MM CENTRES WEATHERBOARD TO BE FIXED WITH A 35MM OVERLAP

PLEASE SEE **WWW.FOXFRAMING.CO.UK** FOR FULL TERMS, CONDITIONS & SPECIFICATIONS RELATING TO FRAME MANUFACTURE & ASSOCIATED GROUND WORKS

DO NOT SCALE FROM THIS DRAWING EXCEPT FOR PLANNING PURPOSES © FOX FRAMING PRINT AT A3

 Rev No:
 Revision:
 Date:

 Image: Constraint of the second of the

5m

DRAWING TYPE: Planning DRAWING NAME: TWO BAY 7.5 x 6m FULL HEIGHT FRAME; PLAN & SPECIFICATIONS