

euro bat



THE BASIS FOR SIMPLE, LOW COST INSTALLATION

- This is the “family founder” of the Genius range. It is easy to install and is very low cost-effective.
- The release system with customized lock enables the leaf to be moved by hand, in case of a power cut.

THE IMPORTANCE OF DIMENSIONS

- Right and left hand versions are available, in order to reduce the pilaster/hinge distance.

VERSATILE AND SAFE: IDEAL FOR ALL APPLICATIONS

- Models with rod travel of 300 and 400 mm are available for fitting leaves up to 4 m.
- All models are non-reversible, ensuring leaf blocking up to 2.50 m even without an electric lock.

- The slow version for very heavy leaves, where a uniform, safe movement is necessary in relation to the leaf’s peripheral speed.
- The 24V models are an important resource to increase the frequency of manoeuvres in case of intensive use.

DIMENSIONS



Power supply 24V recommended for an intensive use.

Model	Version
Euro Bat 324 DX	Non-reversible Right power supply 24 Vdc
Euro Bat 324 SX	Non-reversible Left power supply 24 Vdc
Euro Bat 424 DX	Non-reversible Right power supply 24 Vdc
Euro Bat 424 SX	Non-reversible Left power supply 24 Vdc
Euro Bat 300 DX	Non-reversible Right
Euro Bat 300 SX	Non-reversible Left
Euro Bat 400 DX	Non-reversible Right
Euro Bat 400 SX	Non-reversible Left
Euro Bat 300 DX Lento	Non-reversible Right Slow
Euro Bat 300 SX Lento	Non-reversible Left Slow
Euro Bat 400 DX Lento	Non-reversible Right Slow
Euro Bat 400 SX Lento	Non-reversible Left Slow



Unit 13, West Cannock Way,
Cannock Chase Enterprise Centre,
Hednesford, Cannock WS12 0QW

01543 879116
www.midlandcontrolsystems.co.uk