

Declaration of Performance (DoP)



No. F370-CPR-271022	
Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 370 Advance (F371 Advance, F373 Advance, F377 Advance, F378 Advance, F371 Advance High Top, F377 Advance High Top, F378 Advance High Top)
Intended use of the product:	Roomheater burning solid fuel without water supply
Name and Address of the manufacturer:	Jøtul AS Postboks 1411, 1602 Fredrikstad, Norway Tel.: +47 69 35 90 00 E-mail: post@jotul.no
AVCP: <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i>	System 3
Notified body:	Danish Technological Institute / KIWA
NB-No:	1235 / 0558
Test report no:	300-ELAB-2223-EN / 61675-4
Declared performance:	
Harmonized technical specification	BS EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fuel	Wood logs
Fire safety	
Reaction to fire	A1 Minimum distances, in mm (F 377 Advance, F 377 Advance High Top)
Distance to combustible materials	Rear = 75 (50) Sides = 700 (600) Corner = 450 (450) Front = 1100 (1100) <i>See also the installation instructions</i>
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,06 %] NOx [93 mg/m ³] OGC [45 mgC/m ³] PM [4 mg/m ³]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [275°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	6 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	η [78%]