

Series 4 EV Home Charger

Designed & Built for Use at Home







The SemaConnect Series 4 EV Home Charger is designed for drivers who want to charge their electric vehicle safely and in the privacy of their own home. With innovative features, the Series 4 allows for maximum power delivery, greater convenience, and the advanced technology drivers need to ensure their vehicle is ready to go.

Key Features

- Level 2 Charger (240V) with flexible amperage up to 50A
- WiFi Enabled

- Easy-to-Read OLED Display
- · Long 25-foot Cable
- · Easy Installation

Additional Features

- · Charges up to 37 miles of range per hour
- Flexible configuration: power output level (16-50 A) can be configured to accommodate a range of circuit breakers
- J1772™ Plug is compatible with all EVs and plug-in hybrids
- · Wireless technology allows for easy over-the-air firmware upgrades
- · Phone app pre-schedules sessions, power shares, & locks the station
- NEMA 14-50 electrical plug or hard-wired option
- · Alexa Voice Control: will be compatible in the future
- Fleet-ready: will support power sharing and fleet vehicles in the future





Series 4 EV Charging Station Technical Specification

Power Specs

AC Power Output, maximum Level II: 12kW (240VAC@50A)

AC Power Input Level II: 50A; Line 2 and GND (no neutral)

Ports Per Charging Station One

Vehicle to Charger Connection SAE J1772 EV Connector, 25ft Cable

Energy Metering Accuracy +-1%

Standby Power 3.9W typical

Service Panel Breaker 2-pole, common trip 20-80A circuit breaker

Safety Specs

Safety, Ground Fault Circuit Interrupt 20mA CCID with auto retry (every 15 seconds)

Automatic Plug-Out Detection Pwr terminated per SAE J1772 spec

General Safety Compliance UL 2231-1, 2231-2, UL2594 and NEC Article 625

Network Specs

Data Communication WiFi

Network Communication Protocol OCPP

Network Security HTTPS-WSS; 128 bit AES Encryption

Communication Device Specs

LED Array High visibility, multi-color visual status indication

LED Display Graphical OLED

Environmental Specs

Outdoor Rated NEMA 3R

Operating Humidity Up to 95% non-condensing

Operating Temperature -30 degree C to +50 degree C ambient

Other Specs

Surge Protection 6kV@3,000A

EMI Compliance FCC Part 15 Class B

Dimensions 15" H (21" with cable holder) x 6.25" W x 6" D

Approximate Shipping Weights 15 lbs

Installation / Use Wall Mount / Indoor and Outdoor

Wall and Cable Mount Integrated