

CONSERVATION WHITE

KCV CENTER PIVOT CONSERVATION ROOF WINDOW



VARIANT	911
PANE	
Construction	4-16-4H
Thickness of glazing (mm)	24
Low E	✓✓
Gas	Argon
Toughened	✓
U_g (W/m ² K)	1.0
Total solar energy transmittance	0.55
WINDOW	
U_w (W/m ² K)	1.3
Water tightness	E1350
Air permeability	Class 4
Resistance to wind load	Class C4
Sound reduction	32 (-1,-5) dB
Ventilation valve	✓
COLOUR	
White (painted)	✓



NEXT 20
GUARANTEE



MAX PROTECT



MASTER WOOD

APPLICABLE

- In public, domestic buildings, for conservation area and for old buildings (for renovation)
- In heated, inhabited rooms
- In roof pitch range of 15°-90°
- Suitable on all common roofings with proper flashing

FEATURES

- Center pivot
- Black external profiles and black glazing bar
- Extra sliding gasket
- Ventilation valve
- Two passive ventilation positions via handle
- Easy installation
- 10 + 10 year guarantee

MATERIAL / WOOD AND FINISHING

- Kiln-dried laminated pine wood
- Timber from FSC certified forests
- Fungicide protection
- Water-based white paint

COVER PARTS

- Aluminium, powder coated, Black RAL 9005

HANDLE

- Ergonomically designed moulded zinc handle, powder coated

HINGE

- Centre pivot



TECHNICAL DATA

MEASURES [cm]

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT	EFFECTIVE LIGHT AREA m ²
KCV C2A	55x78	55	77,8	39,8	64,9	37,3	59	0,22
KCV C4A	55x98	55	97,8	39,8	84,9	37,3	79	0,295
KCV F6A	66x118	66	117,8	50,8	104,9	48,3	99	0,478
KCV M4A	78x98	78	97,8	62,8	84,9	60,3	79	0,476
KCV M6A	78x118	78	117,8	62,8	104,9	60,3	99	0,597
KCV M8A	78x140	78	139,8	62,8	126,9	60,3	121	0,729

FLASHING COMPATIBILITY TABLE

ACCESSORIES COMPATIBILITY TABLE

CODE	FLUSH FLASHING VINTAGE (BLACK)	PLAIN TILE FLASHING VINTAGE (BLACK)	UNIVERSAL FLASHING VINTAGE (BLACK)	BLACKOUT BLIND	ROLLER BLIND	VENETIAN BLIND	ANTI - HEAT BLIND	ROLLER SHUTTER
KCV C2A	KFF C2A VINTAGE	KFP C2A VINTAGE	KUF C2A VINTAGE	DUA C2A	RHA CXA	PAA C2A	MIA CXA	SSR C2A
KCV C4A	KFF C4A VINTAGE	KFP C4A VINTAGE	KUF C4A VINTAGE	DUA C4A	RHA CXA	PAA C4A	MIA CXA	SSR C4A
KCV F6A	KFF F6A VINTAGE	KFP F6A VINTAGE	KUF F6A VINTAGE	DUA F6A	RHA FXA	PAA F6A	MIA FXA	SSR F6A
KCV M4A	KFF M4A VINTAGE	KFP M4A VINTAGE	KUF M4A VINTAGE	DUA M4A	RHA MXA	PAA M4A	MIA MXA	SSR M4A
KCV M6A	KFF M6A VINTAGE	KFP M6A VINTAGE	KUF M6A VINTAGE	DUA M6A	RHA MXA	PAA M6A	MIA MXA	SSR M6A
KCV M8A	KFF M8A VINTAGE	KFP M8A VINTAGE	KUF M8A VINTAGE	DUA M8A	RHA MXA	PAA M8A	MIA MXA	SSR M8A

PANE 9

Energy saving insulated glass

4-16-4H

$U_g: 1,0 \text{ W/m}^2\text{K}$

$U_w: 1,3 \text{ W/m}^2\text{K}$

4 mm float glass







Low-E coating [reflects heat]

Argon gas filled cavity

Low-E coating [reflects heat]

4 mm toughened safety glass

AVAILABLE SIZES [cm]

					
C2A	C4A	F6A	M4A	M6A	M8A
55x78	55x98	66x118	78x98	78x118	78x140



CE²⁰
EN 14351-1:2006
+A2:2016

www.dakea.com

