
| existing clay peg tiles shall be carefully removed and set aside for re-use ensuring that | |
|--|-----------|
| | |
| lime mortar pointed verge tile matching tile undercloak | |
| non hydraulic lime render supplied by Best of Lime over chestnut timber laths (12mm thick Warmcote with 8mm thick Limecote) and finished with breathable limewash paint system by Inglby Paints or similar approved, colour subject to client and planning authority approval | |
| Steico Duo Dry t&g wood fibre boards fixed to both existing main timber frame members and battened out at intermediate stud positions, as required | |
| Thermafleece Ultrawool thicknesses (50/70/90) - contractor shall utilise the maximum possible thickness where space allows between studs and in front of wattle daub | |
| South Facing Gable Roof Verge Detail - | Scale 1:5 |
| | |
| Thermafleece Ultrawool thicknesses (50/70/90) - contractor shall utilise the maximum possible thickness where space allows between studs and in front of wattle daub | |
| Steico Duo Dry t&g wood fibre boards fixed to both existing main timber frame members and battened out at intermediate studs positions, as required ———————————————————————————————————— | |
| non hydraulic lime render supplied by Best of Lime over chestnut timber laths (12mm thick Warmcote with 8mm thick Limecote) and finished with breathable limewash paint system by Inglby Paints or similar approved, colour subject to client and planning authority approval | |
| suitable breather membrane over face of wood fibre boards | |
| expamet stainless steel flyscreen strip wrapped around batten ends and allowing ventilation between vertical battens | |
| 450mm min. girth Hyload dpc lapped and bonded with dpm upstand to building footprint perimeter and set within reconstructed plinth wall min. 150mm above existing retained road levels | |
| existing masonry shall be reconstructed in accordance with structural engineers recommendations new bricks shall be handmade soft red bricks bonded lime mortar and flemish bonded with details subject to Planning Authority. approval | |
| N.B reconstructed plinth wall shall follow the profile of the existing wall | YORDURET |
| ground level varies, detail shows ground at its highest level in relation to internal floor level | |
| Platon P20 drainage / ventilation membrane laid against wall from foundation level up to ground level | |
| granular fill surround to perimeter french drain, drain pipe shall be wrapped with geotextile membrane and connected to new surface water drainage system | |
| | |
| underpinning existing load bearing walls in accordance with structural engineers separate design details and specification | |

| | | | tiles shall be relaid over 38 x 25mm horizontal battens over Proctor Roofshield vapou roofing felt over lapping margin of type 5U felt dressed into eaves gutter over 25 x 5 battens laid over rafter positions | | | |
|------------------------------|------------|--|--|---|---|----------------------------|
| | | | Procter Roofsheild vapour permeable roofing membrane counter battens existing and structurally repaired rafters | | | |
| AR. BY | | | | non hydrauli timber laths breathable li | ic lime render supplied by Best of Lime over (12mm thick Warmcote with 8mm thick Lim imewash paint system by Inglby Paints or si ent and planning authority approval ——— | ecote) and finished with |
| | | | Thermafloc VSD membrane or similar approved | | | Outside |
| | mate | ting internal finishes are to be remove erial or finish or retained if of historica | d if of an inappropriate contemporary al value - refer to seperate photographic | breather me | mbrane | |
| | with | an alkali resistant mesh bedded into | d by Best of Lime (8mm thick Warmcote base coat the initial scratch coat with a 5mm thick Limecote finish) to by Inglby Paints or similar, colour to client selection | wall frame, o existing watt | le and daub retained | |
| | | co Duo Dry t&g wood fibre boards fix battened out at intermediate studs po | xed to both existing main timber frame members | existing / re | paired timber vertical stud frame ———— | |
| | | | | | | Inside |
| | | | existing wattle and daub to be retained where currently exists with proposed Thermafleece Ultrawool insulation fitted as may be possible between existing stud wall frame and to fill voids in front of and behind wattle & daub | | | |
| | | | Thermafloc VSD membrane or similar approved | | existing internal finishes are to be remove material or finish or retained if of historicc annotated details. existing retained finishe | al value - refer to seperc |
| | | | Steico Duo Dry t&g wood fibre boards fixed to both existing main timber frame meml and battened out at intermediate studs positions, as required | | Typical Plan Construction | |
| | | | new seasoned oak wall plate to replace existing decayed timber plate with all studs repaired in accordance with separate structural engineers design details | | | |
| | | | Non hydraulic lime plaster system supplied by Best of Lime (8mm thick Warmcote bas with an alkali resistant mesh bedded into the initial scratch coat with a 5mm thick Lime receive breathable limewash paint system by Inglby Paints or similar, colour to client s | ecote finish) t | o | |
| | | | existing internal finishes are to be removed if of an inappropriate contemporary material or finish or retained if of historical value - refer to seperate photographic annotated details. existing retained finishes or otherwise are to be covered over, as d | detailed | | |
| | | | Thermafloc VSD membrane or similar approved lapped over dpc downstand, as indic | cated | | |
| | TBC | | 1200 gauge Visqueen dpm upstand lapped with dpc, as indicated | | | |
| | 22 | | lime mortar bed and pointed brick pammet floor finish - thickness to be confirmed min. 75mm fibre reinforced s/c screed floor with underfloor heating pipe system | | | |
| $\bigcirc \bigcirc \bigcirc$ | | | min. 60mm thick Celotex insulation type board | | | |
| $\setminus / \setminus /$ | \/ \/-\/ = | | 100mm thick Celotex ground floor insulation board over dpm | | | |
| | | | 1200 gauge Visqueen dpm 100mm thickness of mesh reinforced ground bearing oversite slab in accordance with structural engineers specification details | | | |
| | | | | | | |

ALL DIMENSIONS AND LEVELS TO BE CHECKED ON SITE BY MAIN CONTRACTOR PRIOR TO COMMENCING EXCAVATION WORKS. ANY DISCREPENCY IS TO BE REPORTED BACK TO THE DESIGNER FOR INSTRUCTION.

THIS DRAWING IS THE PROPERTY OF SIMON BURKE DESIGN LTD AND MAY NOT BE REPRODUCED OR DISCLOSED TO A THIRD PARTY IN ANY FORM WITHOUT WRITTEN PERMISSION.

Construction Design and Management Regulations Attension is drawn to the requirements of the Construction Design and Management Regulations 2015 and the statutory requirement to notify the HSE of commencement on site via the submission of the F10 registration form. Attention is drawn to the Designers Risk Assessment



oriate contemporary eperate photographic a to be covered over, as detailed

Detail of External Timber Frame Wall le 1:5

TENDER ISSUE

Copyright © Simon Burke Design Ltd

| rev. C | and propos | tructural engineers requirements and to accomodate existing ed external ground levels, paving levels and accomodate wheel rinciple entrance door etc. | 05. 09. 2023 chair |
|---|--------------|---|---|
| rev. B | additional c | letail included | 23. 02. 2023 |
| rev. A | minor detai | l changes | 08. 02. 2023 |
| project | | | project no. |
| The Cottage, School Street, Stoke by Nayland | | 0122 | |
| drawing | | | drawing no. |
| South Facing Gable End Wall / | | | |
| Sout | h Faci | | 3 5 |
| Sout | h Faci | ng Gable End Wall / oor and Roof Verge Details | 3 5 scale |
| Sout | h Faci | | |
| Sout | h Faci | | scale |
| Sout | h Faci | oor and Roof Verge Details | scale 1:5@A1 date |
| Sout | h Faci | SIMON | scale 1:5 @ A 1 |
| Sout | h Faci | SIMON BURKE | scale 1:5@A1 ^{date} Nov. 2022 |