

0

1

Proposed South - West Elevation(1:50)

ROOF:

Cure-IT Flat roof finish (Dark Grey). Code 4 Lead throughout. Fascia/Soffits - Grev

DRAINAGE:

New 68mm Ø PVCu RWP connected into existing drainage, 120mmØ Deepflow RWG - colour: Black. Bracket and support to be fixed at 500m horizontal centres. 1.8m vertical centres

WINDOWS:

Windows to be uPVC External Anthracite Grey / Internal White Optiwhite argon gas filled double glazed with 'KS' inner pane coating with warm air edge spacer (1.4 $\,$ W/m²K U-value). Opening parts shown. Glass in doors and any adjacent windows to be toughened on inside pane; laminated on outer, designed to resist human impact as set in BS6262 Part 4: 2005. Trickle vents to be fitted to opening sashes as shown to achieve 12000mm² rate of ventilation. 25mm Kingspan insulation to be fitted at window jamb, head and cills to prevent thermal bridging

PATIO DOOR SET:

Patio Doors to be External Anthracite Grey / Internal White Optiwhite argon gas filled DOUBLE glazed with 'KS' inner pane coating with warm air edge spacer $(1.40 \text{ W/m}^2\text{K U-value})$. Opening part shown. Glass in doors to be toughened on inside pane; laminated on outer, designed to resist human impact as set in BS 6262 Part 4: 2005. 25mm Kingspan insulation to be fitted at door jamb and head to prevent thermal bridging

WALL:

Beige Blockwork Harled to Basecourse & Beige Fyfestone to Dado & Full Height Wall - to match EXISTING

FASCIA & SOFFIT: Grey uPVC

RAINWATER GOODS: Black uPVC

Any discrepancies or queries regarding any part of of the works to be discussed prior to any affected work being carried out.

Drawings not to be scaled and all sizes to be checked on site.

Lighting / Electrical Items all as per Specification and to final positions to be agreed on site by customer

ANY Sub floor ventilator covered by works to be re-routed to external air

DISCUSSED PRIOR TO ANY AFFECTED WORK BEING CARRIED OUT		
WHILST THE HIGHLIGHTED AREAS ARE INDICATIONS OF SERVICES BELOW GROU THERE MAY BE OTHERS OUT WITH, THEREFORE ALL EXCAVATIONS SHOULD INCORPORATE EXTREME CARE AND DILIGENCE		
DRAWINGS TO BE READ AND UNDERSTOOD PRIOR TO WORK COMMENCING.FIG DIMENSIONS TO TAKE PREFERENCE OVER SCALED DIMENSIONS. ALL DIMENSION LEVELS TO BE CHECKED ON SITE. EXISTING DRAINAGE AND SERVICES POSITIONS CONFIRMED ON SITE.ANY DISCREPANCIES TO BE REPORTED BACK TO ARCHITECT		
CUSTOMER APPROVAL		
SALES ADVISER		
SALES MANAGER		
APPROVAL	DATE	SIGNATURE

3

4

GENERAL NOTES

2

