

Section A

PROPOSED SECTION A

1:100@A3

- Areas to be insulated using breathable insulation and lime plaster finishes.

 Replacement roof structure to be insulated at rafter level. New lime plaster ceiling finishes internally. Existing tiles to be relaid over new breather membrane.

 Proposed retrofit of slimiline double glazed units to existing pionery.

 Proposed ritople glazed window/door behind existing retained shutters

 Underpinning to south wall of stable block at proposed link abutment.

 Existing parapet capping to be removed, brickwork repaired with appropriate mortar. Stepped lead flashing at roof abutment and parapet capping replaced.

 Proposed triple glazed screen with new structural steel columns behind

 Sedum blanket roof.

 Sodum blanket roof.

 Sodum blanket roof.

 Mollow for boarding existing structure with plywood

 Lic issting flat ceilings to be enhanced with additional insulation.

 Proposed conservation rooflight

 Replacement carpet floor finish.

 Tiled floor finish.

 Proposed timber floor finish.

 Proposed timber floor finish.

 Proposed timber floor finish.

 Timber stair with quarter landing.

 Existing window opening enlarged to make door.

 Proposed the plageade hardwood window joinery to suit new/existing opening.

 Proposed triple glazed a hordwood door joinery to suit new/existing opening.

 Proposed triple glazed hardwood door joinery to suit new/existing opening.

 Proposed triple glazed hardwood door joinery to suit new/existing opening.

 Proposed triple glazed hardwood door joinery to suit new/existing opening.

 Proposed triple glazed hardwood door joinery to suit new/existing opening.

 Proposed triple glazed hardwood door joinery to suit new/existing opening.

 Proposed triple glazed hardwood door joinery to suit new/existing opening.

 Proposed triple glazed hardwood door joinery to suit new/existing opening.

 Proposed triple glazed hardwood door joinery to suit new/existing opening.
- Proposed insulated limecrete slab consisting compacted foamglass insulation, lime slab incorporating UFH. Tiled floor finish.

 Proposed insulation between existing joists, retained by new breather membrane. Existing floorboards carefully reinstated (refer to floor finishes plan).

 Existing symment tiles to be carefully removed and reinstated following insulation works.

 Proposed garden wall; refer to landscape plan.

 Proposed secondary glazing installed behind existing window.

 Proposed hard landscaping (indicative); refer to landscape plan.

 Existing stable partitions retained and refurbished.

 Sixting stable partitions retained and refurbished.

 Proposed painted lime render.

 Proposed air source heat pump (indicative; size and spec TBC).

 Widened opening through to bar area.



