


Our REF NGF-7115-23
Date 21st November 2023

Cornwall Council Planning Dept
New County Hall
Treyew Road
Truro
TR1 3AY



ENERGY ACCESS

Building Compliance Consultants

Office 2 Trereife Park Offices
Trereife, Penzance, Cornwall
TR20 8TB
01736 367474

Planning Policy SEC1 Energy Statement for a new dwelling at 'Land South East of Wynroe', Hornick Hill, High Street, St Austell

Executive Summary

This Energy Statement and its attached documents has been prepared in support of a planning application for the proposed new dwelling South East of Wynroe, Hornick Hill, High Street, St Austell. The Energy Statement includes an energy demand assessment illustrating how selected energy efficiency, low carbon and renewable energy measures have been considered and deemed appropriate for the scheme.

Table of Contents

1. Introduction and Qualifications
2. Planning Policy
3. Executive Summary
4. Sustainable Energy Strategy
 - 4.1 Passive Design
 - 4.2 Overheating Mitigation
 - 4.3 Water Efficiency Measures
5. Energy Efficiency
 - 5.2 Space Heating Demand
 - 5.2 Total Energy Use
 - 5.3 Renewable Generation
6. Energy Summary Tool
7. Conclusions



1. Introduction

Energy Access was formed in May 2006 and has evolved significantly during this period of time, to become a market leader in the South West within their field.

Primarily the core business of Energy Access is On Construction Domestic Energy Assessments (SAPs), Energy Performance Certificates (EPCs) and Air Tightness/Pressure testing and the Code for Sustainable Homes.

Qualifications held by Energy Access include a Fellowship of the Royal Charter of Building Engineers (CABE), On Construction Domestic Energy Assessors (Elmhurst), members of The Air Tightness Testing and Measurement Association (ATTMA) & Code for Sustainable Homes Assessor through Stroma.

2. Planning Policy

Policy SEC1 Part 2b states that The Climate Emergency DPD will Guide Cornwall Council in addressing climate change within planning decisions. Policy SEC1 Sustainable Energy and Construction Part 2b focusses on the energy use of new-build homes in a drive towards net zero operational demand. In Summary, the three elements of this are

- A) a space heating energy threshold – 30kWh/m²/year
- B) a total energy threshold – 40kWh/m²/year
- C) a renewable energy requirement – equal or greater than the total energy demand

3. Executive Summary

We have been commissioned by **NGF Architects** to assist with the proposed development of a new dwelling on land South of **Wynroe, Hornick Hill, High Street, St Austell** in calculating and documenting the energy efficiency of the proposed development in support of a Planning Application. This statement includes an energy demand assessment showing how selected energy efficiency, low carbon and renewable energy measures have been considered and those deemed most appropriate for the development.

SAP calculations have been used to show compliance with the Planning requirement for Policy SEC1. These have been prepared for the development based upon the construction specification listed in this report either enclosed or annexed herein.

In accordance with CEDPD Policy SEC1, the data from the SAP calculations were inputted into the required tool (Energy Summary Tool SAP) and below are the findings

CEDPD Policy SEC1	Space Heating Demand kWh/m ² /year	Total Energy Use kWh/m ² /year	Renewable Energy Generation kWh/m ² /year
Wynrose	21.6	23	25.3
Compliance	Pass	Pass	Pass

4. Sustainable Energy Strategy

4.1 Passive Design

The Energy performance of a building is affected by its design, construction, use - whilst the occupant behaviour exceeds the remit of this report. In the first instance the design team has provided a very well insulated building fabric to actually reduce the energy needed to condition the environment thus reducing the heat loss and therefore the use of energy in the form of space heating. This “fabric first” approach is highly recommended in today's construction methodology along the lines of the Passive Design principle.

The following U values have been proposed for the dwelling

- The floor will achieve a U value of 0.12W/m²k
- The walls will achieve a U value 0.17W/m²k
- The horizontally insulated roofs will achieve a U value of 0.09W/m²k
- The windows will be high quality double glazed units with an average U value of 1.2W/m²k
- A target air permeability rate will be 3.00 AP50



- Thermal bridging values (PSI) have been based upon the ROI Building Regulations Accredited details
- A MVHR (Mechanical Ventilation and Heat Recovery Unit) will be used within the dwelling
- An Air Source heat pump will be used to condition the internal environment of the development.
- Low energy lighting installed throughout the project

The dwelling has also been oriented to make the most of the useful solar gains possible from its environment, with openings to capture the day and evening sun and fill the house with solar gains. Adopting the “Passive House” standards the high levels of insulation to the fabric along with the positive solar gains, will actually mean that the Building should require little heating throughout the year.

Furthermore, the high levels of insulation will help retain heat and release it back into the dwelling. This will greatly assist the “passive” heating of the dwelling and further reduce the requirement of the heating system and therefore reduce the CO₂ load.

With regards to the M&E, I would confirm that on this particular build a Low and zero carbon feasibility assessment with regards to high efficiency alternative heating systems for the development has been carried out

The developer has incorporated low and zero technology in this dwelling in the form of an air source heat pump to condition the internal environment.

Items such as wind and hydro were dismissed on the grounds of applicability for the location.

Solar thermal was investigated, but the returns were not high enough to make it viable.

The most logical solution alternative, was to provide a PV array to the house which would give a better reduction in CO₂, and this has also been adopted by the developer within the design.

4.2 Overheating Mitigation

Approved Document O of the Building Regulations stipulates the requirements that every new dwelling must be subject to and pass an overheating assessment. In this instance an assessment has been carried out for the development by the Architect.

4.3 Water Efficiency Measures

Sanitary appliances and whitegoods have not been specified at this early stage of the project. Therefore for the purposes of this assessment, water efficiency has been deemed as meeting the requirements.

Rainwater harvesting will be used in the development, in the form of water butts with the purpose of external irrigation.

5. Energy Efficiency

The proposed scheme has been thermally modelled and assessed within the SAP software (output sheets enclosed) which compares the proposed dwellings performance against a minimum set of targets that are set by the Building Regulations standards. The results have been used as a means of determining the energy target and dwelling results using the approved modelling software Elmhurst SAP 10.

5.1 Space Heating Demand

On the basis of the aforementioned specification, when the out put figures are inputted in to the Councils SAP Energy Summary Tool, it achieves the following result

CEDPD Policy SEC1	Space Heating Demand kWh/m2/year
Wynrose	21.6
Compliance	Pass

As the results are less than 30 kWh/m²/year then the scheme complies with the Councils requirement.

5.2 Total Energy Use

With the air source heat pump as the primary heating system, when the out put figures are inputted in to the Councils SAP Energy Summary Tool, it achieves the following result

CEDPD Policy SEC1	Total Energy Use kWh/m ² /year
Wynrose	23
Compliance	Pass

As the results are less than 40 kWh/m²/year then the scheme complies with the Councils requirement.

5.3 Renewable Generation

A PV array will be provided to the development in order to generate electric within the dwelling and a 5.4kW array has been used on the East elevation

On this basis, when the out put figures are inputted in to the Councils SAP Energy Summary Tool, it achieves the following result

CEDPD Policy SEC1	Renewable Energy Generation kWh/m ² /year
Wynrose	25.3
Compliance	Pass



Compliance has been shown without the use of energy storage however this may be something that is considered either by the client or end user and will only further improve the scheme.

5.4 Energy Summary Tool Worksheet

CEDPD Policy SEC1	Space Heating Demand kWh/m2/year	Total Energy Use kWh/m2/year	Renewable Energy Generation kWh/m2/year
Wynrose	21.6	23	25.3
Compliance	Pass	Pass	Pass

6. Conclusion

In conclusion, it has been demonstrated that this development will be highly efficient (both passively and through the low and zero carbon M&E) to the location and significantly benefit its environment.

The scheme has also been demonstrated to satisfy all the criteria of the Policy SEC1 Part 2b of The Climate Emergency DPD

No off-set payment is considered needed for this development as the renewable energy generation target has been met.

I trust the above and enclosed gives a coherent perspective of the likely environmental impact of this property.

Please do not hesitate to contact me if I can help further

Kind Regards



Stuart Thomas BSc(Hons) C.Build E FCAB

Enclosures

- *SAP Design calculation output sheets*
- *Policy SEC1 Calculations - energy-summary-tool-sap*

Copyright Energy Access (South West) Ltd and not to be used or reproduced without express permission of the author Stuart Thomas BSc(Hons) C.Build E FCAB