


3 stake method for securing trees Scale - 1:20

Girth	Height	Specification
12-14cm	3.0-3.5m	Heavy Standard :Clear Stem 175-200 :Root balled
12-14cm	3.0-3.5m	Heavy Standard :Clear Stem 175-200 :Root balled
12-14cm	3.0-3.5m	Heavy Standard :Clear Stem 175-200 :Root balled
12-14cm	3.0-3.5m	Heavy Standard :Clear Stem 175-200 :Root balled
12-14cm	3.0-3.5m	Heavy Standard :Clear Stem 175-200 :Root balled
	2.5m	Feathered :Root balled
12-14cm	3.0-3.5m	Heavy Standard :Clear Stem 175-200 :Root balled
	12-14cm 12-14cm 12-14cm 12-14cm 12-14cm	12-14cm 3.0-3.5m 12-14cm 3.0-3.5m


Selected to 750mm 3/5 brks :C Selected to 900mm 3/5 brks :C 4/m

Pot Size Height

Height	Specification	Density
20-30cm	Bushy :3/4 brks :C	4/m²
30-40cm	Branched :C	4/m²
60-80cm	Leader With Laterals :5/7 brks :C	Counted
20-30cm	Branched :3/5 brks :C	4/m²
20-30cm	Bushy :3/5 brks :C	3/m²
20-30cm	Bushy :3/4 brks :C	4/m²
30-40cm	Branched :3/4 brks :C	Counted
60-80cm	Branched :3/5 brks :C	3/m²
20-30cm	Bushy :3/5 brks :C	4/m²
20-30cm	Branched :3/5 brks :C	4/m²
125-150cm	Leader With Laterals :5/7 brks :C	Counted
25-30cm	Branched :3/4 brks :C	3/m²
10-20cm	3/4 brks :C	No.
10-20cm	3/4 brks :C	3/m²
10-20cm	Branched :3/4 brks :C	5/m²
10-20cm	Branched :3/4 brks :C	5/m²
	30-40cm 60-80cm 20-30cm 20-30cm 30-40cm 60-80cm 20-30cm 125-150cm 125-150cm 10-20cm 10-20cm	20-30cm Bushy :3/4 brks :C 30-40cm Branched :C 60-80cm Leader With Laterals :5/7 brks :C 20-30cm Branched :3/5 brks :C 20-30cm Bushy :3/5 brks :C 20-30cm Bushy :3/5 brks :C 20-30cm Bushy :3/4 brks :C 30-40cm Branched :3/4 brks :C 30-40cm Branched :3/4 brks :C 30-40cm Branched :3/4 brks :C 20-30cm Bushy :3/5 brks :C 20-30cm Branched :3/4 brks :C 125-150cm Leader With Laterals :5/7 brks :C 125-30cm Branched :3/4 brks :C 10-20cm 3/4 brks :C 10-20cm 3/4 brks :C 10-20cm Branched :3/4 brks :C



Pot Size Density



Planting specification

Imported topsoil is to comply with the British Standard BS 3882:2015 definition for Multipurpose grade topsoil, and is to be accompanied with a test certificate and horticultural analysis summary for approval by the landscape architect prior to delivery to site. Existing subsoil shall conform to BS8601:2013. Required topsoil depths specified below. Provide a minimum of one week's notice. Shrub areas are to receive topsoil minimum 450mm depth after compaction. Grass areas to receive minimum 150mm depth after compaction. Subsoil beneath topsoil areas to be broken up to a depth of 300mm prior to placing topsoil. Avoid mechanical cultivation within the RPA's of existing trees.

Topsoil depths:

Grass turf/seed - 150mm Hedge lines - 450mm

Woodland mix/shrub mix/shrub planting - 450mm Wildflower turf/seed - 100mm

ALL PLANTS - GENERAL

• Condition: Materially undamaged, sturdy, healthy and vigorous • Appearance: Of good shape and without elongated shoots

- Hardiness: Grown in a suitable environment and hardened off • Health: Free from pests, diseases, discoloration, weeds and physiological disorders
- Budded or grafted plants: Bottom worked
- All stock to be supplied bare root if in season. All stock to be supplied in container grown if planted out of season

Trees shall be set in pits 900mm \emptyset x 900mm depth. The base of the tree pit is to be broken up to a depth of 200mm and backfilled with topsoil consolidated in layers to allow the tree to be placed to the correct depth. The pit shall then be backfilled with a mixture of approved topsoil and peat free tree and shrub planting compost at the rate of one part compost to two parts topsoil and 70 -140g/m² Osmocote, Sierrablen Flora 15-9-9 + 3% MgO granular controlled release, or similar approved. Small trees/ Specimen shrubs to be set in 750 x 750mm pits and backfilled with topsoil, compost and fertilizer mix at the rate described for trees above.

Each tree shall be planted to the nursery line and secured by three tree stakes 1.5m in length, 50mm diameter secured with NatureTie biodegradeable webbing. One strap per stake looped around the trunk. Tree stakes shall be driven vertically into firmed ground to a depth of 700mm below the base of the tree pit. After planting all trees shall be thoroughly watered in to field capacity and a 75mm depth layer of Melcourt Ornamental Bark Mulch 5-35mm with minimal dust and fines and less than 5% wood content or similar approved spread over the 332100.

> After planting, thoroughly water to field capacity immediately without damaging or displacing plants or soil. Trees planted in grass are to have a 1m diameter turf cut around the base of the tree and circle filled with bark mulch to 75mm depth.

Hedges

Hedge trenches shall be dug 450mm wide x 450mm deep, the base of which shall be broken up prior to returning the backfill mixture. This shall comprise two parts topsoil to one part peat free tree and shrub planting compost. Stock shall be planted at the distances given in the schedules. All stock shall be planted to the root collar and well firmed in place. Crataegus hedges in public areas shall be planted with biodegradeable Rainbow Treebio spiral guards and canes. All stock to be supplied bare root if in season. All stock to be supplied container grown if planted out of season.

All stock shall be thoroughly watered in to field capacity. After planting, a 75mm layer of 5-35mm Melcourt contract bark mulch shall be spread over the trench to a width of 1m.

Shrub planting (ornamental)

provided on the drawing.

the original specified, stating: Price; difference from specified plants/ trees. Obtain approval before making any substitution. All shrub beds shall be topped up with good quality topsoil to ensure 450mm planting depth the base ground being thoroughly broken up before placement. Tree and shrub planting compost shall be spread to a minimum depth of 75mm and in addition evenly spread, 70 -140g/m² Osmocote, Sierrablen Flora 15-9-9 + 3% MgO granular controlled release, or similar approved, thoroughly working in during cultivation. Shrub planting pits should be 150 mm wider than roots when fully spread. Backfill with excavated material.

After planting, thoroughly water to field capacity immediately without damaging or displacing plants or soil. Lightly firm soil around plants and rake soil to a fine tilth with gentle cambers and no hollows. Avoid damaging plants. A 75mm depth layer of Melcourt ornamental Bark Mulch 5-35mm with minimal dust and fines and less than 5% wood content or similar approved spread is to be spread over entire bed. The mulch shall be free of pests, disease, fungus and weeds.

After initial planting, supply and spray Grazers G1 to ornamental planting then every 6 weeks for the duration of the 12-month maintenance contract.

Native Shrub belt Mix

Woodland shrub beds shall be soiled with good quality topsoil to a depth 300mm. Evenly spread 70 -140g/m² Osmocote, Sierrablen Flora 15-9-9 + 3% MgO granular controlled release, or similar approved, thoroughly working in during cultivation. Each woodland mix plant shall be planted in a 600mm GT Greenguard tree tube with one stake per plant. www.green-tech.co.uk Spaced at 1.2m centres.

All stock to be supplied bare root if in season. All stock to be supplied in containers if planted out of season. Mulched over whole bed to 75mm depth with 5-35mm Melcourt fine bark mulch.

<u>Grass - turf</u>

Rolawn Medallion[®] turf to BS3936

Supplier: Rolawn Ltd www.rolawn.co.uk

All areas to be turfed shall be topsoiled to a minimum depth of 150mm over ground free of compaction by cultivation. The soil shall be fine graded to even running falls and cross raked to form a fine tilth. Before turfing an approved pre-turfing fertilizer shall be applied in accordance with the manufacturer's instructions. All edges to shrub beds will be cleanly cut with an edging iron, arisings removed from site.

Grass - seed

A4 - Low Maintenance Areas seed mixture Supplier: Germinal www.germinal.com

Sowing rate: 35g per m²

All areas to be seeded shall be topsoiled to a minimum depth of 150mm over ground free of compaction by cultivation. The soil shall be fine graded to even running falls and cross raked to form a fine tilth. Broadcast at rate to 35g/m². Rake/harrow seed mix into the soil to a maximum depth of 10mm.

Maintenance

Carry out the operations in the following clauses for a period of 12 months from the date of practical completion. Plants/ trees/ shrubs that have failed to thrive (unless due to theft or malicious damage) within the 12-month period from the date of practical completion will be replaced with equivalent plants/ trees/ shrubs to match the original. Remove soil and arisings from hard surfaces and grassed areas. Generally leave the works in a clean tidy condition at Completion and after any maintenance operations.

Maintain weed free area around each tree and shrub. Keep planting beds clear of weeds. Take care not to reduce depth or effect of mulch. Gently firm loosened soil around trees/ shrubs. Straighten leaning trees/ shrubs. Tighten and straighten stakes if required. Prune to promote healthy growth and natural shape removing: Dead, dying, diseased wood and suckers. Remove arisings. Trim and shape each specimen appropriately to species, location, season, and stage of growth, leaving a well-balanced natural appearance. Cut back herbaceous material in autumn.

All shrub beds shall be thoroughly watered as necessary for the continued thriving of all planting. In times of water shortage obtain instructions before proceeding. Re-mulch at the end of the 12-month maintenance period to a depth of 75mm ensuring that the soil is thoroughly moistened prior to

re-mulching. All planting shall be maintained in good order throughout the initial establishment period. Visits: Twice a month between May and September and a total of three visits between October and April.

Spot treat persistent weeds with glyphosate-based translocated herbicide in accordance with manufacturer's instructions and in compliance with all necessary legislation and regulations using appropriately qualified staff. All arisings are to be removed from site.

Grass areas

Grass areas are to be cut 18 times per year and the cuttings collected up and removed from site. Native shrub belt mix planting

Areas shall be maintained weed and litter free at all times and shelters regularly checked for firmness. Any stakes that fail shall be replaced. All stock shall be watered in during periods of drought. At the end of the growing season each plant shall receive an application of slow release fertilizer. Any plants that die or fail to thrive shall be replaced with stock to the original specification. At the end of the defects period all trees and shrubs shall be inspected and any found to be dead or failing shall be replaced with stock to the original specification. Mulch shall be topped up to 75mm depth.

• Root system and condition: To requirements of National Plant Specification and balanced with branch system.

All shrubs shall be set out to the positions shown on the drawing and to the densities given. All stock shall comply with the specification

Plants unobtainable or known to be likely to be unobtainable at time of ordering: Submit alternatives which offer the closet possible match to

DESIGN RISK: PROJECT-SPECIFIC SIGNIFICANT RISKS							
#	Hazard/Risk	Mitigation/ Residual Risk					
1	Underground/ overhead cables & services	Contractor's responsibility to check the location of underground services prior to carrying out works.					
2	-	-					
3	-	-					
4	-	-					
5	-	-					
	·						

Key

SF Soft Landscaping				
	Grass - turf			
	Grass - seed			
	Ornamental bed planting			
A A A A A A A	Proposed hedge			
•	Large specimen shrub			
	Proposed tree heavy standard 12-14cm girth			
\otimes	Groups of 3no. Hydrangea			
* A * B	Groups of planting beneath existing trees			
$\begin{array}{c} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 &$	Groups of bulbs beneath existing trees			
	50mm depth composted bark mulch beneath existing trees			
Key				
SF Surface Edgings				
	Existing Breedon gravel topped up to proposed levels			
	Tobermore Textured Flags 450 x 450 x 50mm, Natural			

Indian Sandstone flags to match existing, random rectangular bond, 10mm mortar joints

Terram Bodpave 85 - see DT01

Class 4 Vacuum high pressure treated timber gravel board and peg edging to BS EN 335:2013

FOR INFORMATION

С	22.11.23	Minor adjustme	nts to key	IB	MS		
В	15.11.23	Dimension of st	eps confirmed	IB	MS		
A	08.09.23	Changes to conf planning officer		IB	MS		
Rev.	Date	Comments		Drawn	Chkd		
SMEEDEN FOREMAN Landscape Architecture • Ecology • Arboriculture Somerset House, Low Moor Lane, Scotton, Knaresborough, North Yorkshire, HG5 9JB www.smeedenforeman.co.uk tel: 01423 863 369							
Project 5 Grove Lane, Headingley Title Hard and soft landscape proposals							
Proi	ect No.	Drawing No.		Re	v.		
	3188	LL01		(2		
Scale 1:200 Scale @ A0		Date 12.09.00					
Drawn by IB			Checked by MS				
Smeed	den Foreman Limite	ed. Copyright reserved.	I tial and the drawing is the e No use, copy or disclosure of ed to Smeeden Foreman Limit.	the drawing	may be		

meeden Foreman Limited takes no responsibility for the use of this drawing for any purpose othe than for that which it was intended. This drawing must be read in conjunction with all other related drawings and documentation All dimensions are in millimeters unless stated otherwise. All dimensions should be verified on site prior to commencement of wo Do not scale from this drawing.

All works including materials must be in accordance with British Standards, EC Standards, Health & Safety at work act & all other relevant regulations & Bye Laws. All products to be used in accordance with the manufacturer's recommendations Smeeden Foreman Limited has not checked or verified, and shall therefore not be liable for any accuracies which may be attributable to any in been utilised within this drawing. Any discrepancies should be brought to the attention of Smeeden Foreman Limited.

The locations of above and below ground utilities equipment, if shown, have been reproduced from plans supplied to Smeeden Foreman Limited by third parties. Although care has been taken when duplicating this information, these locations are approximate only. It is the client's or its appointed ontractor's responsibility to accurately locate any utilities equipment on site by appropriate

neans prior to carrying out any mechanical excavation or other relevant operations.