

THE ~~AT~~RY, CASH/CIN/TU

Date
11/23

Job No.
23/4199

Page

SUCRAPE WATER DRAINAGE

Office
AN

Engineer
SH


Checked

SELF BUILD SCHEME
(7 UNITS)



DATE:

THIS DRAWING IS THE PROPERTY OF LUNDI ARCHITECTS LTD AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF LUNDI ARCHITECTS LTD. THIS DRAWING IS THE PROPERTY OF LUNDI ARCHITECTS LTD AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF LUNDI ARCHITECTS LTD.



THE DAIRY, CATHERINGTON


DATE:	
PROJECT:	PETER ERNEST HOMES LTD
DESCRIPTION:	SELF BUILD DEVELOPMENT - 7 UNITS THE DAIRY, CATHERINGTON, HANTS
DATE:	AUGUST 2023
SCALE:	1:50 @ A1, 1:100 @ A2
PROJECT NO.:	LA2332_013
DATE:	

LUNDI ARCHITECTS

LUNDI ARCHITECTS LTD
100, THE STABLES
CATHERINGTON, HANTS
RG24 0EX
01256 343434
www.lundiarchitects.co.uk

SCALE

THIS PLAN IS FOR INFORMATION ONLY AND DOES NOT REPRESENT A CONTRACT. THE ARCHITECT'S OFFICE SHALL NOT BE RESPONSIBLE FOR ANY CONSTRUCTION DEFECTS OR OMISSIONS. THE CLIENT SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE LOCAL AUTHORITY AND OTHER RELEVANT AGENCIES. THE ARCHITECT'S OFFICE SHALL NOT BE RESPONSIBLE FOR ANY DELAYS OR COST INCREASES DUE TO CHANGES IN REQUIREMENTS OR UNFORESEEN OBSTACLES. THE ARCHITECT'S OFFICE SHALL NOT BE RESPONSIBLE FOR ANY DAMAGE TO THE SITE OR SURROUNDING AREAS. THE ARCHITECT'S OFFICE SHALL NOT BE RESPONSIBLE FOR ANY ACCIDENTS OR INJURIES OCCURRING ON THE SITE OR SURROUNDING AREAS. THE ARCHITECT'S OFFICE SHALL NOT BE RESPONSIBLE FOR ANY LOSS OF PROFITS OR BUSINESS. THE ARCHITECT'S OFFICE SHALL NOT BE RESPONSIBLE FOR ANY OTHER DAMAGES. THE ARCHITECT'S OFFICE SHALL NOT BE RESPONSIBLE FOR ANY OTHER CONSEQUENCES. THE ARCHITECT'S OFFICE SHALL NOT BE RESPONSIBLE FOR ANY OTHER DAMAGES. THE ARCHITECT'S OFFICE SHALL NOT BE RESPONSIBLE FOR ANY OTHER CONSEQUENCES.



Plot 4
326 sqm



THE DAIRY, CATHERINGTON

PROJECT	THE DAIRY, CATHERINGTON - HARTS
CLIENT	PETER ERNEST HOMES LTD
DATE	AUGUST 2023
SCALE	1:50 @ A1 1:100 @ A3
PROJECT NO.	LA2332 014
DATE	
BY	
CHECKED BY	
DATE	
PROJECT NO.	
DATE	
BY	
CHECKED BY	
DATE	

LUNDI ARCHITECTS

LUNDI ARCHITECTS LTD
100 CATHARTON ROAD
CATHERINGTON, HANTS GU52 5JY
www.lundiarchitects.co.uk
info@lundiarchitects.co.uk

THE DAIRY, CATHLAMTOUR

Date
11/23

Job No.
23/4192

Page

SURFACE WATER DRAINAGE

Office
RW

Engineer
BH

Checked

SELF BUILD SUITONE

PLOT 1

m².

Roof $94.0 + 21.0 = 117.0$

C/PACKET $37.0 = 37.0$

154.0 m²

PLOTS 2-5

Roof $(110.0 + 21.0) \times 4 = 524.0$

C/PACKET $37 \times 4 = 148.0$

672.0 m²

PLOTS 6 & 7

Roof $(86.0 + 21.0) \times 2 = 214.0$

C/PACKET $37.0 \times 2 = 74.0$

288.0 m²

VISITOR'S C/PACK.

(F) _H $7.7 \times 5.8 = 44.7 \text{ m}^2$

THE DAIRY, CANNINGTON

Date
11/25

Job No.
23/197

Page

SUBFACE WATER DRAINAGE

Office
CW

Engineer
BH

Checked

COMMERCIAL UNIT

			m ²
(A) _R	10.8 x 4.9	=	74.5
(B) _R	4.6 x 1.5	=	6.9
(C) _H	10.4 x 5.2	=	54.1
(D) _H	5.2 x 2.6	=	13.5
			<hr/>
			149.0 m ²

ACCESS ROAD

			m ²
(1) _H	5.0 x 10.9	=	109.6
(2) _H	6.1 x 6.0	=	57.6
			<hr/>
			626.2 m ²



THE DAIRY, CATHLAMTON

Date
11/23

Job No.
23/4197

Page

SULLAGE WATER DRAINAGE

Office
BW

Engineer
BH

Checked

SELF BUILD SCHEME (ADUACOM)

PLOT 1 (SA1)

157.0 m² PCC PLOT

FROM COMPACT FINISH OUT

ADAPT 2.0m x 2.5m x 1.2m BELOW
INLET INLET LEVEL.

COMMERCIAL UNIT (SA2)

149.0 m² PCC PLOT

FROM COMPACT FINISH OUT

ADAPT 2.0m x 2.5m x 1.2m BELOW
INLET INLET LEVEL.

ACCESS ROAD / VISITORS / PLOTS 2-5 (SA3)

$$672.0 + 44.7 + 626.2 = 1342.9 \text{ m}^2$$

FROM COMPACT FINISH OUT

ADAPT 1.0m x 43.0 x 1.2m BELOW INLET
INLET LEVEL.

PLOTS 6 & 7 (SA1)

144.0 m² PCC PLOT

FROM COMPACT FINISH OUT ADAPT

2.0m x 2.5m x 1.2m BELOW
INLET INLET LEVEL

**Tekla Tedds**

Hamill Davies Limited

Ivydale

Lower Chase Road

Swanmore, Southampton SO32 2PB

Project

The Dairy, Catherington

Job no.

23/4197

Calcs for

Self Build (7 units) - Plot 1

Start page no./Revision

1

Calcs by

B.H.

Calcs date

17/11/2023

Checked by

Checked date

Approved by

Approved date

SOAKAWAY DESIGN**In accordance with BRE Digest 365 - Soakaway design**

Tedds calculation version 2.0.04

Design rainfall intensity

Location of catchment area Other ✓
 Impermeable area drained to the system $A = 154.0 \text{ m}^2$ ✓
 Return period Period = 100 yr
 Ratio 60 min to 2 day rainfall of 5 yr return period $r = 0.350$
 5-year return period rainfall of 60 minutes duration $M5_{60\text{min}} = 18.0 \text{ mm}$
 Increase of rainfall intensity due to global warming $p_{\text{climate}} = 50 \%$

Soakaway / infiltration trench details

Soakaway type Rectangular
 Minimum depth of pit (below incoming invert) $d = 1200 \text{ mm}$ ✓
 Width of pit $w = 2522 \text{ mm}$ ✓
 Length of pit $l = 2000 \text{ mm}$ ✓
 Percentage free volume $V_{\text{free}} = 95 \%$
 Soil infiltration rate $f = 130. \times 10^{-6} \text{ m/s}$
 Wetted area of pit 50% full $a_{s50} = l \times d + w \times d = 5426965 \text{ mm}^2$

Table equations

Inflow (cl.3.3.1) $I = M100 \times A$
 Outflow (cl.3.3.2) $O = a_{s50} \times f \times D$
 Storage (cl.3.3.3) $S = I - O$

Duration, D (min)	Growth factor Z1	M5 rainfalls (mm)	Growth factor Z2	100 year rainfall, M100 (mm)	Inflow (m ³)	Outflow (m ³)	Storage required (m ³)
5	0.36;	9.6;	1.90;	18.3;	2.82;	0.21;	2.61
10	0.51;	13.7;	1.97;	26.9;	4.15;	0.42;	3.72
15	0.62;	16.7;	2.00;	33.4;	5.14;	0.63;	4.50
30	0.79;	21.2;	2.03;	43.0;	6.62;	1.27;	5.35
60	1.00;	27.0;	1.99;	53.8;	8.29;	2.54;	5.75
120	1.22;	33.0;	1.95;	64.3;	9.90;	5.08;	4.82
240	1.50;	40.4;	1.89;	76.2;	11.74;	10.16;	1.58
360	1.69;	45.6;	1.84;	84.2;	12.96;	15.24;	0.00
600	1.95;	52.6;	1.79;	94.2;	14.51;	25.40;	0.00
1440	2.48;	67.0;	1.69;	113.5;	17.48;	60.96;	0.00

Required storage volume

$S_{\text{req}} = 5.75 \text{ m}^3$

Soakaway storage volume

$S_{\text{act}} = l \times d \times w \times V_{\text{free}} = 5.75 \text{ m}^3$

PASS - Soakaway storage volume

Time for emptying soakaway to half volume

$t_{s50} = S_{\text{req}} \times 0.5 / (a_{s50} \times f) = 1\text{hr } 7\text{min } 56\text{s}$

PASS - Soakaway discharge time less than or equal to 24 hours

**Tekla Tedds**

Hamill Davies Limited

Ivydale

Lower Chase Road

Swanmore, Southampton SO32 2PB

Project

The Dairy, Catherington

Job no.

23/4197

Calcs for

Self Build (7 Units) - Commercial Unit

Start page no./Revision

1

Calcs by

B.H.

Calcs date

29/09/2023

Checked by

Checked date

Approved by

Approved date

SOAKAWAY DESIGN**In accordance with BRE Digest 365 - Soakaway design**

Tedds calculation version 2.0.04

Design rainfall intensity

Location of catchment area Other
 Impermeable area drained to the system $A = 149.0 \text{ m}^2$ ✓
 Return period Period = 100 yr
 Ratio 60 min to 2 day rainfall of 5 yr return period $r = 0.350$
 5-year return period rainfall of 60 minutes duration $M5_{60\text{min}} = 18.0 \text{ mm}$
 Increase of rainfall intensity due to global warming $p_{\text{climate}} = 50 \%$

Soakaway / infiltration trench details

Soakaway type Rectangular
 Minimum depth of pit (below incoming invert) $d = 1200 \text{ mm}$ ✓
 Width of pit $w = 2428 \text{ mm}$ ✓
 Length of pit $l = 2000 \text{ mm}$ ✓
 Percentage free volume $V_{\text{free}} = 95 \%$
 Soil infiltration rate $f = 130. \times 10^{-6} \text{ m/s}$
 Wetted area of pit 50% full $a_{s50} = l \times d + w \times d = 5313286 \text{ mm}^2$

Table equations

Inflow (cl.3.3.1) $I = M100 \times A$
 Outflow (cl.3.3.2) $O = a_{s50} \times f \times D$
 Storage (cl.3.3.3) $S = I - O$

Duration, D (min)	Growth factor Z1	M5 rainfalls (mm)	Growth factor Z2	100 year rainfall, M100 (mm)	Inflow (m ³)	Outflow (m ³)	Storage required (m ³)
5	0.36;	9.6;	1.90;	18.3;	2.73;	0.21;	2.52
10	0.51;	13.7;	1.97;	26.9;	4.01;	0.41;	3.60
15	0.62;	16.7;	2.00;	33.4;	4.97;	0.62;	4.35
30	0.79;	21.2;	2.03;	43.0;	6.41;	1.24;	5.17
60	1.00;	27.0;	1.99;	53.8;	8.02;	2.49;	5.54
120	1.22;	33.0;	1.95;	64.3;	9.58;	4.97;	4.60
240	1.50;	40.4;	1.89;	76.2;	11.36;	9.95;	1.41
360	1.69;	45.6;	1.84;	84.2;	12.54;	14.92;	0.00
600	1.95;	52.6;	1.79;	94.2;	14.04;	24.87;	0.00
1440	2.48;	67.0;	1.69;	113.5;	16.91;	59.68;	0.00

Required storage volume

$S_{\text{req}} = 5.54 \text{ m}^3$

Soakaway storage volume

$S_{\text{act}} = l \times d \times w \times V_{\text{free}} = 5.54 \text{ m}^3$

PASS - Soakaway storage volume

Time for emptying soakaway to half volume

$t_{s50} = S_{\text{req}} \times 0.5 / (a_{s50} \times f) = 1\text{hr } 6\text{min } 51\text{s}$

PASS - Soakaway discharge time less than or equal to 24 hours

Project The Dairy, Catherington				Job no. 23/4197	
Calcs for Self Build (7 units) - Plot 6 & 7				Start page no./Revision 1	
Calcs by B.H.	Calcs date 17/11/2023	Checked by	Checked date	Approved by	Approved date

SOAKAWAY DESIGN

In accordance with BRE Digest 365 - Soakaway design

Tedds calculation version 2.0.04

Design rainfall intensity

Location of catchment area Other
 Impermeable area drained to the system $A = 144.0 \text{ m}^2$ ✓
 Return period Period = 100 yr
 Ratio 60 min to 2 day rainfall of 5 yr return period $r = 0.350$
 5-year return period rainfall of 60 minutes duration $M5_{60\text{min}} = 18.0 \text{ mm}$
 Increase of rainfall intensity due to global warming $p_{\text{climate}} = 50 \%$

Soakaway / infiltration trench details

Soakaway type Rectangular
 Minimum depth of pit (below incoming invert) $d = 1200 \text{ mm}$ ✓
 Width of pit $w = 2333 \text{ mm}$ ✓
 Length of pit $l = 2000 \text{ mm}$ ✓
 Percentage free volume $V_{\text{free}} = 95 \%$
 Soil infiltration rate $f = 130. \times 10^{-6} \text{ m/s}$
 Wetted area of pit 50% full $a_{s50} = l \times d + w \times d = 5199608 \text{ mm}^2$

Table equations

Inflow (cl.3.3.1) $I = M100 \times A$
 Outflow (cl.3.3.2) $O = a_{s50} \times f \times D$
 Storage (cl.3.3.3) $S = I - O$

Duration, D (min)	Growth factor Z1	M5 rainfalls (mm)	Growth factor Z2	100 year rainfall, M100 (mm)	Inflow (m ³)	Outflow (m ³)	Storage required (m ³)
5	0.36;	9.6;	1.90;	18.3;	2.64;	0.20;	2.43
10	0.51;	13.7;	1.97;	26.9;	3.88;	0.41;	3.47
15	0.62;	16.7;	2.00;	33.4;	4.80;	0.61;	4.19
30	0.79;	21.2;	2.03;	43.0;	6.19;	1.22;	4.98
60	1.00;	27.0;	1.99;	53.8;	7.75;	2.43;	5.32
120	1.22;	33.0;	1.95;	64.3;	9.25;	4.87;	4.39
240	1.50;	40.4;	1.89;	76.2;	10.98;	9.73;	1.25
360	1.69;	45.6;	1.84;	84.2;	12.12;	14.60;	0.00
600	1.95;	52.6;	1.79;	94.2;	13.57;	24.33;	0.00
1440	2.48;	67.0;	1.69;	113.5;	16.34;	58.40;	0.00

Required storage volume

$$S_{\text{req}} = 5.32 \text{ m}^3$$

Soakaway storage volume

$$S_{\text{act}} = l \times d \times w \times V_{\text{free}} = 5.32 \text{ m}^3$$

PASS - Soakaway storage volume

Time for emptying soakaway to half volume

$$t_{s50} = S_{\text{req}} \times 0.5 / (a_{s50} \times f) = 1\text{hr } 5\text{min } 36\text{s}$$

PASS - Soakaway discharge time less than or equal to 24 hours