

**114X7084****Optyma™ Slim Pack, OP-MSBM034AJW05G**

Type designation: Condensing Units, Type: Optyma™ Slim Pack, Model Number:

OP-MSBM034AJW05G, Refrigerant: R404A; R448A; R449A; R452A; R507, Segment usage:

Medium Back Pressure, No. of phases (compressor): 1

PRODUCT DETAILS

Gross weight	78 kg
Net weight	63 kg
EAN	5702428562140
Air flow @ 50Hz [m³/h]	3300 m ³ /h
Applications	MBP
Approval standard	CE EAC
Compressor model	CAJ4519Z
Compressor power supply [V/Ph/Hz]	230/1/50
Condenser type	D7
Description	OP-MSBM034AJW05G
Electrical code	G
Fan blade size [mm]	450 mm
Fan cowl/grill type	B2
Fan current @ 50Hz [A]	0.47 A
Fan diameter [mm]	450 mm
Fan power consumption @ 50Hz [W]	110 W
Fan power output @ 50Hz [W]	68 W
Fan power supply [V/Ph/Hz]	230/1/50
Fan voltage @ 50Hz (max) [V] [Max]	230 V
Fan voltage @ 50Hz (max) [V] [Min]	230 V
Length [mm]	464 mm
Liquid line connection [in]	1/2 in
Liquid line connection type	Solder
MCC	15.2 A
Model Number	OP-MSBM034AJW05G
No. of phases (compressor)	1
No. of phases (fan)	1
Number of fans	1
Receiver approval	CE
Receiver volume [L]	3.4 L
Refrigerant	R404A R449A R452A R507 R448A
Region	Europe
Segment usage	Medium Back Pressure

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Optyma™ Slim Pack, OP-MSBM034AJW05G
PRODUCT DETAILS

Sound power @ 50Hz [db(A)]	68 dBA	
Sound pressure level 50Hz (@10 m distance) [db(A)]	37 dBA	
Suction connection size [in]	1/2 in	
Suction connection type	Solder	
Technology	Reciprocating	
Total height [mm]	690 mm	
Type	Optyma™ Slim Pack	
Type designation	Condensing Units	
Version	W05	Optyma Slim Pack - Standard version
Voltage 50Hz [V]	220 V	
Voltage 50Hz [V] [Max]	240 V	
Width [mm]	1087 mm	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

061H3140 [🔗](#)
Fan speed controller, XGE-4C

Factory setting [bar]: 19.00, Number of Phases: 1, P band max. [bar]: 6.0, Regulation range [bar] Pe [Min]: 10.00, Regulation range [bar] Pe [Max]: 25.00, Type designation: XGE-4C


061H3142 [🔗](#)
Fan speed controller, XGE-4CB

Factory setting [bar]: 19.00, Number of Phases: 1, P band max. [bar]: 6.0, Regulation range [bar] Pe [Min]: 10.00, Regulation range [bar] Pe [Max]: 25.00, Type designation: XGE-4CB

Spare Parts

118U3878 [🔗](#)
Electrical equipment

Overload relay SCHNEIDER-LRE21+LAEB2


118U5168 [🔗](#)
Housing equipment

Sheet Metal Left Side B2

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**118U3484** [🔗](#)**Fan cowl**

Fan cowl ø 457 mm

**118U3994** [🔗](#)**Compressor**

CAJ4519Z compressor

**118U0051** [🔗](#)**Electrical equipment**

Crankcase heater 55Watt

**118U5146** [🔗](#)**Housing equipment**

Sheet Metal Top B2

**118U5147** [🔗](#)**Housing equipment**

Sheet Metal Fan B2

**023Z5041** [🔗](#)**Hermetic filter drier, DML**

Product name: Hermetic filter drier, Inlet connection type: Flare, Outlet connection type: Flare

**118U3475** [🔗](#)**Condenser**

Receiver 3,4L

**118U3823** [🔗](#)**Fan motor**

Fan motor

**118U5148** [🔗](#)**Housing equipment**

Sheet Metal Back B2

**118U5170** [🔗](#)**Fusible plug**

NPT receiver

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**014L0173** [🔗](#)**Sight glass, SGP 12 N**

Inlet size [mm]: 12.00, Inlet connection type: Flare, Outlet size [mm]: 12.00, Outlet connection type: Flare

**118U3297** [🔗](#)**Electrical equipment**

Capacitor 3,5 µF

**060-539766** [🔗](#)**Pressure Switch, KP17WB**

Product name: Pressure Switch, Type: KP17WB, Contact function: SPDT+SPST(NO), Pressure connection size: 1/4, Pressure connection type: Flare, Pressure Male/Female: Male

**118U5218** [🔗](#)**Condenser**

MCHX condenser D7 for B2/H2

**118U5149** [🔗](#)**Housing equipment**

Sheet Metal Service Panel B2

**118U3481** [🔗](#)**Fan blade**

Fan blade

**118U3896** [🔗](#)**Electrical equipment**

Contact kit SCHNEIDER-LC1E40M7

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.