

- 1. All dimensions in millimetres unless otherwise shown.
- 2. All levels in metres above Ordinance Datum (mAOD) unless otherwise shown. 3. All dimensions to be checked on site and any discrepancies reported to Landscape Architect or
- Employer before pricing / work starts. 4. Any ambiguities or discrepancies within this drawing and any other information given elsewhere
- must be reported to the Landscape Architect or the Employer for clarification prior to pricing or construction works commencing.
- 5. All drawings to be read in conjunction with other drawings and specification information as
- 6. Refer to relevant Engineer's and Architect's information as appropriate for confirmation of all engineering and architectural details (including base and sub-base formation layers).
- 7. All works to be carried out in accordance with the latest British Standards and appropriate codes of practice as a minimum.
- 8. Unless noted as Construction Status, all information shown is NOT for construction. Clarification to be sought from the Landscape Architector the Employer prior to construction works commencing

VENTILATION GRATING FOR EXISTING FACADE BRICK VENTS (VG)

Nominal 300x300mm opening ductile iron grating with max. 10mm wide openings for 'heelsafe'

Ductile iron grating and frame to be finished in Black.

Gratings to be aligned with brick vents in building facade and paving coursing, alignment to have some flexibility to ensure paving cuts minimised. Overall frame size at paving level to be between 390mm-400mm to allow for alignment with paving

Plenum below grating must allow for sufficent free air-area required and have adequate drainage, to

SWR SWR P00 14/07/2023 First Issue SR Landscape Architecture

Paving Detail - Basement Vent Grille

Checked by: (S1) Issued for co-ordination P00 1:20 @ A1 14/07/2023 53CA07-SRLA-TH-GF-DT-L-0312