



This drawing is the property of SBK. Copyright is reserved by them and this drawing is issued on the condition that it is not copied either wholly or in part without the consent in writing of SBK. This drawing must be read in conjunction with the project specification. Do not scale from this drawing, use figured dimensions only. This drawing was generated using AutoCad.

- NOTES**
- This drawing is to be read in conjunction with all relevant Architects, Engineers and other specialist details and specifications.
  - Drawing issued for preliminary discussions only, further to approval from Client. Following receipt of further information and comments the scheme may be revised.
  - Drawing based upon REV-A Architects layout drawing: SHE17056-REVA-DR-A-SK7 rev P01.2
  - Topographical Survey data drawing is from Battlefield Land Surveys Ltd dated May 2023. The survey information used in the preparation of this drawing is not warranted. The contractor shall check all dimensions and levels on site.
  - The location and level of all existing services are to be identified prior to construction and the engineer advised of any clashes.
  - Works within public highway are subject to section 184 Agreement with the Local Authority.
  - The Contractor is responsible for arranging all necessary road opening and traffic management licenses under the NRSWA.
  - Surface levels to tie in smoothly with existing.
  - Drainage gully positions are indicative and to be located at low points to be agreed on site.
  - Tactile paving positions to be agreed on site with local Authority Highways Inspector.
  - The pavement construction is based on the depths and ground condition assumptions stated on the standard details drawing.
  - If sub-grade material is frost susceptible the full carriageway construction thickness is to be no less than 450 mm.
  - All re-used fill must comply with Class 1 or 2 Acceptable Earthworks Material, in accordance with table 6/1 of 'Specification for Highway Works', and be suitably placed and compacted in accordance with table 6/4.
  - All road markings shall be in accordance with Traffic Signs Regulations & General Directions, and be thermoplastic material or paint complying with BS EN 1871, BS EN 1436. All shall be reflective & skid resistant.

| Rev. | Amendments  | Date     | By | Chkd. |
|------|-------------|----------|----|-------|
| P01  | First Issue | 20.06.23 | DG | AH    |



Civil & Structural Consultants  
45 Frederick Street, Birmingham, B1 3HN  
Email: officeadmin@sbkconsult.com

Drawing Status  
**PRELIMINARY**

**Lime Kiln Cottage, Welshpool**

**S184 Plan 2**

| Drawing Number             | Revision         |
|----------------------------|------------------|
| <b>SBK-23-118-DR-C-551</b> | <b>P01</b>       |
| Drawn by DG                | Checked by AH    |
| Date 19.06.2023            | Scale 1:100 @ A1 |