



| LANDSCAPE KEY | |
|---------------|---|
| P1 | P1 - MACADAM FOOTPATH. SUPPLIER: TARMAC OR EQUAL. SUB-BASES TO BE TESTED ON SITE PRIOR TO INSTALLATION TO DETERMINE SUITABILITY. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| P2 | P2 - CONCRETE AND MACADAM PARKING BAY SURFACES TO BE RETAINED & MARK GOOD WHERE REQUIRED. SUB-BASES TO BE INSTALLED TO ENGINEERS SPECIFICATION. |
| P3a | P3a - CONCRETE AGGREGATE PAVING. SUPPLIER: MARSHALLS OR EQUAL. PRODUCT: CONSERVATION X. COLOUR: SILVER. SUB-BASES TO BE INSTALLED TO ENGINEERS SPECIFICATION. |
| P3b | P3b - CONCRETE AGGREGATE PAVING. SUPPLIER: MARSHALLS OR EQUAL. PRODUCT: CONSERVATION X. COLOUR: CHARCOAL. SUB-BASES TO BE INSTALLED TO ENGINEERS SPECIFICATION. |
| P4 | P4 - BLACK MACADAM ROAD SURFACE. SUPPLIER: TARMAC OR EQUAL. COLOUR: BLACK. SUB-BASES TO BE TESTED ON SITE PRIOR TO INSTALLATION TO DETERMINE SUITABILITY. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| P5 | P5 - INFORMAL MOWN FOOTPATH. |
| P6 | P6 - GRAVEL SUPPLIER: CED. PRODUCT: QUARTZ GRAVEL. DIMENSIONS: 20MM LAID INTO A CLEAR PLASTIC 30MM ECCENTRIC CELL SYSTEM (SUPPLIER SPECIFIED) TO REDUCE MOVEMENT WITH AN ADDITIONAL 20MM COVER TO HIDE CELL SYSTEM. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| P7 | P7 - SYNTHETIC GRASS SUPPLIER: CASAGRASS, MAMORGRASS OR EQUAL APPROVED. PRODUCT: HOLLAND PARK, ELISE OR EQUAL APPROVED. INSTALLED TO SUPPLIERS RECOMMENDATION WITH SHOCKPAD TO REQUIRED DEPTH TO ALLOW FOR PLAY EQUIPMENT FALL HEIGHTS. SUB-BASE TO ENGINEERS SPECIFICATION. |
| E1 | E1 - CONCRETE EDGE SUPPLIER: MARSHALLS OR EQUAL. DIMENSIONS: L 915MM X W 50MM X D 150MM. HAUNCHING TO SUPPLIERS RECOMMENDATION. FOUNDATION TO ENGINEERS SPECIFICATION. |
| E2 | E2 - METAL EDGE SUPPLIER: ALUEXCEL OR EQUAL APPROVED. PRODUCT: (1010) FLEXIBLE & (1010) RIGID. DIMENSIONS: H 75MM X W 10MM X BEAD THICKNESS 6.5MM. MATERIAL: ALUMINIUM. CONCRETE HAUNCHING TO STRUCTURAL ENGINEERS SPECIFICATION. INSTALLED TO MANUFACTURERS SPECIFICATION. |
| PL1 | PL1 - EXISTING PLAY EQUIPMENT RETAINED. POSITION ADJUSTED TO WORK WITH THE PROPOSED LAYOUT. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| PL2 | PL2 - TRAMPOLINE. SUPPLIER: EIBE PLAY OR EQUAL. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| PL3 | PL3 - MARBLE TABLE. SUPPLIER: TIMBERPLAY. PRODUCT: 11-01500. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| PL4 | PL4 - BALL LABYRINTH. SUPPLIER: TIMBERPLAY. PRODUCT: 9-15100. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| PL5 | PL5 - BASKET SWING. SUPPLIER: TIMBERPLAY. PRODUCT: CRADLE NEST (H 1400) OR EQUAL APPROVED. TIMBER AND GALVANIZED STEEL CONSTRUCTION. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| PL6 | PL6 - BOULDERS AND SUPPLIER: CED STONE OR EQUAL. PRODUCT: GJALAN. BOULDERS. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| PL7 | PL7 - TABLE TENNIS TABLE. SUPPLIER: BUTTERFLY PARK. TABLE: TENNIS TABLES CO UK. PRODUCT: BUTTERFLY PARK POLYMER CONCRETE TABLE. POLYMER CONCRETE CONSTRUCTION WITH STEEL CLAD HEAVY DUTY POLYMER PLAYING SURFACE AND ALUMINIUM NET. TO BE ROOT FIXED AS PER STRUCTURAL ENGINEERS SPECIFICATION AND SUPPLIERS RECOMMENDATION. |
| PL8 | PL8 - FOUR IN A ROW. SUPPLIER: TIMBERPLAY. PRODUCT: 9-15000. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| PL9 | PL9 - PARS GAME. SUPPLIER: TIMBERPLAY. PRODUCT: 9-15200. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| PL10 | PL10 - STONE ABACUS. SUPPLIER: GORIC OR EQUAL APPROVED. PRODUCT: STONE ABACUS OR EQUAL APPROVED. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| B1 | B1 - PICNIC BENCH LOCATED WITHIN PLAY AREA & COMMUNITY GARDEN. FSC CERTIFIED HARDWOOD. SUPPLIER: STREETLIFE OR EQUAL. PRODUCT: ROUGH AND READY OR EQUAL WITH ARMRESTS. DIMENSIONS: L 2300MM SEAT HEIGHT: H 450MM. ROOT FIXED TO SUPPLIERS RECOMMENDATION. |
| B2 | B2 - LINEAR SEAT LOCATED WITHIN PLAY AREA. FSC CERTIFIED HARDWOOD. SUPPLIER: STREETLIFE OR EQUAL. PRODUCT: ROUGH AND READY 6 OR EQUAL WITH BACKREST & ARMRESTS. DIMENSIONS: L 2300MM SEAT HEIGHT: H 430MM. ROOT FIXED TO SUPPLIERS RECOMMENDATION. |
| B3 | B3 - CIRCULAR TREE SEAT LOCATED AROUND PROPOSED FEATURE TREE & FSC CERTIFIED HARDWOOD. SUPPLIER: STREETLIFE OR EQUAL. PRODUCT: ROUGH AND READY CIRCULAR BENCH OR EQUAL WITH BACKRESTS. DIMENSIONS: Ø 2000MM SEAT HEIGHT: H 450MM. ROOT FIXED TO SUPPLIERS RECOMMENDATION. |
| SU | STEP UNITS. SUPPLIER: MARSHALLS. PRODUCT: CONSERVATION X. STEP UNITS. DIMENSIONS: W 1500MM X D 400MM X H 150MM. COLOUR: SILVER W/CONTRAST STRIP. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| H1 | H1 - HORIZONTAL TO BE GRADE 316 STAINLESS STEEL WITH SATIN BRUSHED FINISH. HEIGHT ABOVE PITCH LINE TO BE 900MM. HORIZONTAL TO BE 50MM DIAMETER WITH ADDITIONAL LOWER HORIZONTAL FOR EXTRA SUPPORT IF REQUIRED. TO BE MOUNTED TO STEP SURFACE USING STAINLESS STEEL WITH COVER TO FABRICATORS SPECIFICATION. |
| F1 | F1 - FENCE AND GATE LOCATION AROUND PLAY AREA. SUPPLIER: JACKSONS FENCING. PRODUCT: BOWTIE ANTI TRIP METAL RAILINGS. COLOUR: RAL 6002 - LEAF GREEN. DIMENSIONS: PANEL HEIGHT: H 1200MM. POST Ø 30MM DIAMETER. RAILS: 50MM X 25MM. POST CENTRES: 2700MM. PALES: 190MM. GATE POSTS: 80MM X 80MM. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| F2 | F2 - PROPOSED COORDINATED FENCING ON EXISTING BRICK WALLS WITH MATCHING TIMBER GATES. TO BE COORDINATED SITE WISE TO GIVE A UNIFORM APPEARANCE AND IMPROVE PRIVACY FOR RESIDENTS. VERTICAL TIMBER FENCE. DIMENSIONS: TOTAL HEIGHT 1800MM. SUPPLIER: JACKSONS FENCING OR EQUAL. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| F3 | F3 - REPLACEMENT PERIMETER FENCING. TO BE COORDINATED SITE WISE TO GIVE A UNIFORM APPEARANCE AND IMPROVE PRIVACY FOR RESIDENTS. VERTICAL TIMBER FENCE. DIMENSIONS: TOTAL HEIGHT 1800MM. SUPPLIER: JACKSONS FENCING OR EQUAL. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| BST | BST - PROPOSED BIN STORE. SPECIFICATION TO BE COORDINATED WITH VERTICAL ENTRANCE DETAIL TO CREATE A UNIFORM APPEARANCE. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| BS2 | BS2 - PROPOSED BIN STORE. SPECIFICATION TO BE COORDINATED WITH VERTICAL ENTRANCE DETAIL TO CREATE A UNIFORM APPEARANCE. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| CL | CL - CYCLE LOCKER. SUPPLIER: CYCLEWORKS. PRODUCT: VELO STORE. MATERIAL: POWDERCOATED STEEL. ROOT FIXED TO SUPPLIERS RECOMMENDATION. |
| CS | CS - CYCLE STAND. SUPPLIER: MARSHALLS OR EQUAL. PRODUCT: SHEPHERD CYCLE STAND. MATERIAL: GALVANIZED STEEL. ROOT FIXED. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| MC | MC - MOTORCYCLE SPACE. IDENTIFIED USING EITHER A PAVED SURFACE OR BLOCK PAVING COLOUR VARIATION FROM SURFACE. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| DR | DR - DRYERS. ROOT FIXED. INSTALLED TO SUPPLIERS RECOMMENDATION. |
| VB | VB - VEGETABLE BEDS. CONSTRUCTED USING 200MM X 100MM SLEEPERS ON EDGE. MATERIAL: HARDWOOD SLEEPERS. OVERALL DIMENSIONS: L 2500MM X W 1500MM H 450MM. |
| BW | BW - WAYFINDING SIGN. SUPPLIER: IS GROUP. PRODUCT: WAY200 TOTEM CONFIGURATION 3 OR 4. DIMENSIONS: H 2200MM X D 1400MM. AREA B - TOUGHENED GLASS OVER MAP AREA D - POWDERCOATED WITH BLUE/RED/GREEN. |
| SI | SI - SIGN INFORMATION. SUPPLIER: IS GROUP. PRODUCT: WAY200 TOTEM CONFIGURATION 3 OR 4. DIMENSIONS: H 2200MM X W 400 X D 1400MM. AREA B - TOUGHENED GLASS OVER MAP AREA A - POWDERCOATED WITH BLUE/RED/GREEN. TO INCLUDE: <ul style="list-style-type: none"> • YOU ARE HERE LOCATION ON MAP • BLOCK LAYOUT PLAN WITH FLAT NUMBERS • LOCATION OF PLAY AREA, TRIANGLE GARDEN, DRYING AREA, COMMUNITY GARDEN & GREEN LINK SPACE. |
| GT | GT - GRASS TURF. GRASS SPECIES A SPECIFICATION AS PER SCHEDULE. LAY ON 150MM MINIMUM DEPTH OF AMELIORATED TOPSOIL TO BS 3882 WITH A PH OF 6.5 - 7.2. |
| MIX A | MIX A - HIGH QUALITY AMENITY MIX. PLANTING SPECIFICATION AS PER SCHEDULE. PLANT IN 450MM MINIMUM DEPTH OF AMELIORATED TOPSOIL TO BS 3882 WITH A PH OF 6.5 - 7.2. INSTALLED WITH 50MM DEPTH OF ORNAMENTAL BARK MULCH. |
| MIX B | MIX B - HARDY URBAN PLANTING MIX. PLANTING SPECIFICATION AS PER SCHEDULE. PLANT IN 450MM MINIMUM DEPTH OF AMELIORATED TOPSOIL TO BS 3882 WITH A PH OF 6.5 - 7.2. INSTALLED WITH 50MM DEPTH OF ORNAMENTAL BARK MULCH. |
| H1 | H1 - HEDGE PLANTING SPECIFICATION AS PER SCHEDULE. PLANT IN 450MM MINIMUM DEPTH OF AMELIORATED TOPSOIL TO BS 3882 WITH A PH OF 6.5 - 7.2. INSTALLED WITH 50MM DEPTH OF ORNAMENTAL BARK MULCH. |
| EXV | EXV - EXISTING VEGETATION TO BE RETAINED WHERE POSSIBLE. WHERE APPROPRIATE INFILL PLANTING TO BE INSTALLED USING AMELIORATED TOPSOIL TO BS 3882 WITH A PH OF 6.5 - 7.2. INSTALLED WITH 50MM DEPTH OF ORNAMENTAL BARK MULCH. |
| GS | GS - GREEN SCREEN ALONG EXISTING BOUNDARY FENCE. SUPPLIER: MOBILANE OR EQUAL. PRODUCT: 1000MM X 1000MM SPECIES: HEDERA HELIX 'WHITE RIPPLE'. PLANT IN 450MM MINIMUM DEPTH OF AMELIORATED TOPSOIL TO BS 3882 WITH A PH OF 6.5 - 7.2. INSTALLED WITH 50MM DEPTH OF ORNAMENTAL BARK MULCH. |
| PROPOSED | PROPOSED TILIA PLICATA (RED CEDER) TREE. GIRTH: 25-30. HEIGHT: 10M. CLIMB STRIP: 100MM MINIMUM. TO BE PLANTED IN Ø 2M CIRCULAR TREE PIT. 1000MM MINIMUM DEPTH OF AMELIORATED TOPSOIL TO BS 3882 WITH A PH OF 6.5 - 7.2. 50MM DEPTH OF ORNAMENTAL BARK MULCH. UNDERGROUND DRAINED WITH WATERING SYSTEM. |
| EXISTING | EXISTING TREES TO BE RETAINED. |
| EXISTING | EXISTING TREES TO BE RETAINED. |
| PROPOSED | PROPOSED ADDITIONAL LINEAR DRAIN TO REMOVE SURFACE WATER FROM NEW CAR PARKING AREA. DRAINAGE ENGINEER TO CONFIRM LOCATION. |
| EXISTING | EXISTING LEVELS. |
| PROPOSED | PROPOSED LEVELS. |