



- (1) Brick chimney with clay pots
- (2) Clay tiled roof

(6) Defective render to be replaced

(3) Lead dormer side walls

(7) Decorative stone columns

(8) Brickwork

- (4) Painted timber dentil eaves
- (5) Refurbished timber frame windows with leaded lights - secondary glazing to north elevation

GENERAL NOTES

External Walls

- Strip off all unnecessary services.
- Repoint where necessary, clean brickwork.
- demolition.
- New areas of external wall/infill to be in brick reclaimed from elsewhere on the building/site.

<u>Render Walls</u>

• Patch repair render where necessary and paint.

Ironwork

• Overhaul and redecorate.

<u>Roof</u>

• Make like for like repairs with clay tiles/slates to match on pitches, hips etc. Strip off flat roof and replace with single ply membrane with applied lead rolls.

- Renew all leadwork, flashings etc.
- Cap chimney. Overhaul rainwater goods replace like for like where necessary.
- Vent tiles to be added where necessary.

Doors

• Assess condition of existing doors and where necessary carry out like for like repairs or replace with period appropriate replacements.

<u>Windows</u>

• Assess on individual basis. Overhaul, carry out like for like repairs or replace with similar existing windows to be draught stripped, new windows to be double glazed.

loinery

• Overhaul, carry out like for like repairs.

Services

Ventilation via opening windows.

