



Lower Ground Floor Flat



ELECTRICS KEY:-

Double socket Single socket

Landlords lockable socket Lockable Single socket

External socket

Spur socket (HL=High level)

Dual voltage shaver socket

Cooker switch

500

One way switch

Two way switch 3 ح Three way switch

O_NN Switch with neon indicator

Smoke alarm Heat alarm

Carbon monoxide alarm - installed **M** to Gas safe regulations ****** Mechanical vent

Mechanical vent isolator switch

TV point and socket for Sky

вΤ British telecom VM

Virgin Media

Multiplex plate - 2x double socket, BT, 2x Satellite, TV, BT, and Pre wired for Sky Q

Electric consumer unit E.M Electricity meter

Door Entrance System

Audiophone Linked to Door Entrance Systeem

External fire alarm sounder

B Door bell

Boiler control

1 Thermostat

Gas point in floor

(F) Frost stat

(U) Under floor heating thermostat

UHM UHM Under floor heating manifold

Multi gang switch

Low level pendant light

ONT Optical network termination BBU Battery backup unit

RJ45 CAT 6 RJ45 point

Energy efficient enclosed bulkhead

Energy efficient ceiling light on landlords circuit on timer switch with DDS integrated PIR and dusk till dawn

Kickspace heater Satellite wiring - Refer to clients specification

Energy efficient ceiling light

Energy efficient wall light

downlighter

Energy efficient pendant light

Low voltage energy efficient

Energy Efficient downlighter

Energy efficient mirror light cabinet with shaver socket

Fluorescent tube light

PIR within lantern

dawn to dusk sensor

Cover plate for future light

Passive infra-red sensor

light on timer switch

communal liahtina

dual fuel element

including guard

Outside Tap

Electric ladder towel rad

Wet system ladder towel rad with

Electric panel heater with fused spur

Tubular heater within cupboard

Thermostatic electric shower

Energy efficient strip lights

Radiator

on timer switch

☐ PIR

 \otimes

Mains voltage ceiling track with energy efficient 4 way spotlights

Energy efficient ext. soffit light

External energy efficient wall light

Energy efficient external light with

Directional passive infra-red sensor

Energy efficient communal ceiling

Energy efficient communal wall light

Energy efficient emergency ceiling

light on landlords circuit with battery backup on timer switch for normal

use with integrated PIR and dusk till

dawn sensors. Emergency lighting system to be combined with main

External energy efficient wall light with

Energy Efficient downlighter with fan

D-EVC Electric Vehicle charging point

NOTES

All switches 1200 above F.F.L. to top of plate unless otherwise stated

All sockets 450 above F.F.L. to underside of plate unless otherwise stated

Carbon Monoxide detectors to be installed in strict accordance with specified manufacturers requirements. ensure Carbon Monoxide detectors are installed within the proximity identified within then manufacturer's literature.

TV/FM Aerial wire only each point back to the loft area. Cables to be labelled and secured centrally to a trussed rafter adjacent to the loft hatch.

DISCLAIMER: This drawing is copyright and the property of Trinity Rose Architecture Itd and information is not to be disclosed or reproduced. All dimensions are millimetres, you should not scale from the drawing unless for planning purposes and use figured dimensions where shown. If you are in doubt or the contents of the drawing are not suitable please ask. Please use this drawing in conjunction with all consultants information and site specifications.



Preliminary

Brentor Property Group

11 Cumberland Place Southampton SO15 2BH

Lower & Ground Floor Electrical & Heating Layout

1:100 @ A3 B23-1249-P-209 July 2023