



VIEWED FROM OUTSIDE

Specification/Notes:
 System:
 Fineline System 22 Sliders
 Finish: Polyester powder coated
 RAL Colour: TBC matt
 Mastic: By others after our installation

Glazing: $u = 1.2w/m^2k$ (Centre Pane)
 32mm Double glazed units
 Comprising:
 10mm Clear toughened HST outer
 16mm Argon filled cavity
 (Black Spacers)
 6mm Clear toughened HST soft coat
 low E inner

Fittings:
 Standard in line straight D handles
 Ø19 x 300 Brushed Stainless Steel.

Deadlock to cill.
 Euro profile cylinder keyed both sides.
 Secondary plunge lock internally.

Provide a second locking point in track
 so that the door can be locked with a
 clear opening of 60mm.

Trickle vents (2no. 340mm long)
 Supplied by RW Simon to achieve
 2000mm² free air per vent.



© Copyright reserved by Fineline Aluminium.
 No reproduction of this drawing without prior
 permission.

D	
C	
B	
A	
00	XX/XX/XX Initial Issue Drawing
Rev:	Date: Description:

FINELINE
 ALUMINIUM

Unit T, Aisecome Way, Weston-Super-Mare,
 North Somerset, BS22 8NA

Tel: 01934 429922 Fax: 01934 416796
 www.finelinealuminium.co.uk
 email: info@finelinealuminium.co.uk

Site Details:
 Site Name
 Address Line 1
 Address Line 2
 Address Line 3
 Address Line 4

Architect: *****

Contract Number:	Drawing Number:
FL1234	FE-01
Drawing Name: Slider/Slider Flush threshold	
Dwg Scale:	Drawn By: ???
1:10 @ A1	Reviewed By: JJS
1:20 @ A3	
Date: XX/XX/XX	Revision: 00

Client Signature..... Date.....