

Building Regulations England Part L (BREL) Compliance Report

Approved Document L1 2021 Edition, England assessed by Array SAP 10 program, Array

Date: Wed 06 Mar 2024 17:00:53

Project Information			
Assessed By	Andrew Simpson	Building Type	Bungalow, Detached
OCDEA Registration	EES/027445	Assessment Date	2024-03-06

Dwelling Details			
Assessment Type	As designed	Total Floor Area	50 m ²
Site Reference	14 Pilgrims View	Plot Reference	14 Pilgrims View
Address	14 Pilgrims View, Guildford, GU12 6HU		

Client Details	
Name	Graham Powell
Company	Imageon Designs Ltd
Address	La Cannerie, Morainville Jouveaux, France, 27260

This report covers items included within the SAP calculations. It is not a complete report of regulations compliance.

1a Target emission rate and dwelling emission rate			
Fuel for main heating system	Electricity		
Target carbon dioxide emission rate	13.44 kgCO ₂ /m ²		
Dwelling carbon dioxide emission rate	3.95 kgCO ₂ /m ²		OK
1b Target primary energy rate and dwelling primary energy			
Target primary energy	71.83 kWh _{PE} /m ²		
Dwelling primary energy	41.57 kWh _{PE} /m ²		OK
1c Target fabric energy efficiency and dwelling fabric energy efficiency			
Target fabric energy efficiency	49.4 kWh/m ²		
Dwelling fabric energy efficiency	42.7 kWh/m ²		OK

2a Fabric U-values				
Element	Maximum permitted average U-Value [W/m ² K]	Dwelling average U-Value [W/m ² K]	Element with highest individual U-Value	
External walls	0.26	0.17	Walls (1) (0.18)	OK
Party walls	0.2	N/A	N/A	N/A
Curtain walls	1.6	N/A	N/A	N/A
Floors	0.18	0.11	Ground floor (0.11)	OK
Roofs	0.16	0.11	Roof (1) (0.11)	OK
Windows, doors, and roof windows	1.6	1.2	Door (1.2)	OK
Rooflights	2.2	N/A	N/A	N/A

2b Envelope elements (better than typically expected values are flagged with a subsequent (!))		
Name	Net area [m ²]	U-Value [W/m ² K]
Exposed wall: Walls (1)	10.962	0.18
Exposed wall: Walls (2)	49.1415	0.17
Ground floor: Ground floor, Ground floor	50	0.11
Exposed roof: Roof (1)	50	0.11

2c Openings (better than typically expected values are flagged with a subsequent (!))				
Name	Area [m ²]	Orientation	Frame factor	U-Value [W/m ² K]
Door, Door	1.89	South	N/A	1.2
Window, Window	1.476	South	0.7	1.2
Window, Window	1.476	South	0.7	1.2
Window, Window	1.476	South	0.7	1.2
Window, Window	1.476	South	0.7	1.2
Window, Window	7.0665	East	0.7	1.2
Window, Window	0.54	North	0.7	1.2
Window, Window	1.296	North	0.7	1.2

2d Thermal bridging (better than typically expected values are flagged with a subsequent (!))
Building part 1 - Main Dwelling: Thermal bridging calculated from linear thermal transmittances for each junction

Main element	Junction detail	Source	Psi value [W/mK]	Drawing / reference
External wall	E2: Other lintels (including other steel lintels)	Government-approved scheme	0.023 (!)	RCD
External wall	E3: Sill	Government-approved scheme	0.02 (!)	RCD
External wall	E4: Jamb	Government-approved scheme	0.015 (!)	RCD
External wall	E5: Ground floor (normal)	Government-approved scheme	0.06	RCD
External wall	E10: Eaves (insulation at ceiling level)	Government-approved scheme	0.059	RCD
External wall	E12: Gable (insulation at ceiling level)	Government-approved scheme	0.043	RCD
External wall	E16: Corner (normal)	Government-approved scheme	0.041	RCD
External wall	E17: Corner (inverted - internal area greater than external area)	Government-approved scheme	-0.076	RCD

3 Air permeability (better than typically expected values are flagged with a subsequent (!))

Maximum permitted air permeability at 50Pa	8 m ³ /hm ²	
Dwelling air permeability at 50Pa	4 m ³ /hm ² , Design value	OK
Air permeability test certificate reference		

4 Space heating

Main heating system 1: Heat pump with radiators or underfloor heating - Electricity

Efficiency	356.4%
Emitter type	Underfloor
Flow temperature	35°C
System type	Heat Pump
Manufacturer	Daikin Europe NV
Model	EDLA06EV3
Commissioning	

Secondary heating system: N/A

Fuel	N/A
Efficiency	N/A
Commissioning	

5 Hot water

Cylinder/store - type: Cylinder

Capacity	150 litres
Declared heat loss	1.6 kWh/day
Primary pipework insulated	Yes
Manufacturer	
Model	
Commissioning	

Waste water heat recovery system 1 - type: N/A

Efficiency	
Manufacturer	
Model	

6 Controls

Main heating 1 - type: Time and temperature zone control by arrangement of plumbing and electrical services

Function	
Ecodesign class	
Manufacturer	
Model	

Water heating - type: Cylinder thermostat and HW separately timed

Manufacturer	
Model	

7 Lighting

Minimum permitted light source efficacy	75 lm/W	
Lowest light source efficacy	805 lm/W	OK
External lights control	N/A	

8 Mechanical ventilation		
System type: N/A		
Maximum permitted specific fan power	N/A	
Specific fan power	N/A	N/A
Minimum permitted heat recovery efficiency	N/A	
Heat recovery efficiency	N/A	N/A
Manufacturer/Model		
Commissioning		
9 Local generation		
N/A		
10 Heat networks		
N/A		
11 Supporting documentary evidence		
N/A		
12 Declarations		
a. Assessor Declaration		
This declaration by the assessor is confirmation that the contents of this BREL Compliance Report are a true and accurate reflection based upon the design information submitted for this dwelling for the purpose of carrying out the "As designed" assessment, and that the supporting documentary evidence (SAP Conventions, Appendix 1 (documentary evidence) schedules the minimum documentary evidence required) has been reviewed in the course of preparing this BREL Compliance Report.		
Signed:	Assessor ID:	
Name:	Date:	
b. Client Declaration		
N/A		