

hydropave tegula



ISO 9001:2008

ISO 14001:2004

timeless elegance

- Functions as a SUDS paving system
- Tumbled to give an aged, antique appearance
- Evokes timeless style and elegance
- Vibrant long-lasting colours
- Significantly reduced efflorescence
- Suitable for both modern or period properties

product specifications

Product type	Concrete Paving Block
Manufactured to	BS EN 1338:2003
Surface Layer	Hard wearing surface layer with a minimum layer of 4mm and >350kgs/m ² cement
Frost Protection	Yes
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Drainage Void Width	60mm: 5% to accommodate correct grit grading, reduced maintenance and maximise drainage flow rate 80mm: 6% to accommodate correct grit grading, reduced maintenance and maximise drainage flow rate
Permeability	60mm: 29,000 litres/sec/hectare 80mm: 35,000 litres/sec/hectare
Strength	> 3.6MPa
Slip/Skid resistance	Extremely Low (>75 USRV)
Installed to	BS 7533-3:2005
BSI Plus	Q24 115
Applications	Residential and Commercial when used in conjunction with the correct sub-base design in accordance with the latest British Standard.
Energy used	100% renewable energy
Water used	100% water used from rainwater harvesting system
Carbon Footprint	60mm: 24kgCo ² e/m ² 80mm: 34kgCo ² e/m ²
Recyclable	100% of this product can be recycled
Design Life	25 years - The correct design and aggregates must be used in accordance with the relevant British Standard or any design guidance provided.
Manufacturing location	Produced in the UK with locally sourced materials
breem rating www.bre.co.uk	60mm: A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved by using a recycled sub-base. 80mm: B , according to the Green Guide to Specification, 4 th Edition 2009. A , can be achieved by using a recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2008 quality system. Manufacturing facilities are accredited to ISO14001:2004 Environmental Management. The company publish Environmental labels and declarations in accordance with BS EN ISO 14021:2001.

colours



The swatches below are for colour reference only. The actual block profile for Hydropave Tegula Duo will be as per swatches above.



Hydropave Tegula Duo Bracken

product	size (mm)	colours available	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight (kg) per pack
HYDROPAVE TEGULA 200	200 x 100 x 80	Bracken, Charcoal, Heather	SPECIAL ORDER	9.6	1.6	50	480	1732
HYDROPAVE TEGULA 240 BIM	240 x 120 x 80	Bracken, Charcoal, Heather, Slate	SPECIAL ORDER	10.08	2.02	34.72	350	1781
HYDROPAVE TEGULA DUO BIM	208 x 173 x 60	Bracken, Cedar, Charcoal, Heather, Natural, Slate	YES	12.87	0.99	30	195	1721
(both sizes in one pack)	173 x 173 x 60						195	

BIM This product is available to download from our website in **BIM Level 2** format.

Refer to all instructions and warnings on our website