



ROOF LIGHTS on pitch roof
 Rooflights to be double glazed + to meet 'U' value of min. 2.0 W/m sq.K.
 All roof lights to be A-A fire rated.

Double up rafters on the side of opening, supporting double trimmers above & below opening. Bolt together with M12 bolts at 450 c/s.
 Must be 450mm minimum clear opening with non opening fasteners.

Slim line frame for pitched roof. Reset within roof tiles. Can be fixed to roof pitch as low as 12 deg. & as high as 90 deg.



FLAT ROOF LIGHT
 VELUX or similar slim line aluminium roof light

To be double glazed + to meet 'U' value of min. 2.0W/m sq.K. All roof lights to be A-A fire rated.



Fully thermally broken construction.

Double up rafters on the side of opening, supporting double trimmers above & below opening. Bolt together with M12 bolts at 450 c/s.

Fixed in accordance with the manufacturers instructions.

- New internal walls
- New external walls
- Walls to be demolished
- New doors/windows
- Proposed work shaded
- Rooflight

Neighbours garage
 42 Sandy Lodge Way



38 Sandy Lodge Way


NEIGHBOURING EXAMPLES

This application seeks to follow an identical approval achieved at the neighbours property - 38 Sandy Lodge Way
 REF - 22/0980/FUL
 Images shown on drawing no. 10


14 **PROP LOFT PLAN**
 Scale: 1:100



tel : 0796 222 3141
 email : sandeep@sskarchitects.co.uk



scale - 1 : 100 @ A3



PROPOSED

Purpose - Householder planning application

All dimensions to be checked on site. All omissions & discrepancies to be reported to the designer. © SSK architects owns the copyright of this drawing which must not be reproduced in whole or part without the written permission.	PROJECT: 40 Sandy Lodge Way, HA6 2AS	DATE: 10/04/2024
	DWG NO: PROP LOFT 14	REVISION: