SEWAGE TREATMENT

SEPTIC TANKS BY TRICEL -TRICEL VENTO

OVERVIEW

 $\textbf{High strength and durability} \ \text{characteristics make up the Vento septic tank}.$

This market-leading product has a **super low profile** giving the added benefit for installations as it **requires a smaller excavation**.

This feature, combined with its **lightweight** quality, ensures ease of installation, making it the ideal choice for all septic tank applications.

The Tricel Vento is a **reliable** wastewater treatment solution and an **effective treatment alternative** to sewage treatment plants.

SEPTIC TANK KEY BENEFITS:

- Shallow Dig Tank (the shallowest tank on the market)
- EU Certified to EN12566-1
- Excellent value for money
- Made from a **lightweight Polyethylene**: reducing the cost of transportation and installation
- Large range of sizes available in one tank format. 6-person up to 20-person dwellings.
- · Easy to transport and install
- · Easy, simple and reliable
- Tested to the highest quality standards

• 10 years warranty from the date of purchase







Contact us



Instant Webchat

軭 <u>(/ sewage- treatment/ tricel- environmental- uk/)</u>

MEET OUR TEAM. (/SEWAGE-TREATMENT/TRICEL-ENVIRONMENTAL-UK/)

To find a technician in your area, visit our page

v (https://thelab.tricel.eu/)

VISIT OUR VIRTUAL SHOWROOM. (HTTPS://THELAB.TRICEL.EU/)



HOW DO SEPTIC TANKS WORK?

Step 1

Wastewater flows by gravity into the tank. It is diverted downwards with a T piece, where the solids and heavier material settle to the unit's base. A small amount of anaerobic breakdown occurs at this stage.

Step 2

The filter on the outlet prevents large solids from entering the drainage field. The lighter solids float to the top and form scum layer. An outlet pipe fitted to the unit ensures that only the liquid element flows into the drainage field. This filter and this specially designed dip pipe prevents the scum from passing into the drainage field, which may result in blocked pipes.


Step 3

The effluent exits the septic tank for final treatment in the subsoil as it penetrates through the specially designed drainage field.

Contact us today!







RANGE OF SEPTIC TANKS

Many sizes are available in one tank format, from 6 to 20-person dwellings. Other septic tank sizes are available on request.



Tricel Vento 6 (3,080 litres)

$\eta \;\; \underline{\text{Technical information}}$

Capacity: 3,080 litres

Lengh: 2,700 mm

Width: 1,190 mm

Height: 1,440 mm

Inlet invert height: 1,180 mm

+ Brochure



Tricel Vento 12 (4,000 litres)

η Technical information


(https://tricel.co.uk/sewage-treatment) Capacity: 4,000 litres

treatment)

Lengh: 2,040 mm Width: 1,850 mm Height: 1,540 mm

Inlet invert height: 1,220 mm

+ Brochure





<u>Privacy</u>

η Technical information

Capacity: 5,000 litres

Lengh: 2,430 mm

Width: 1,850 mm

Height: 1,540 mm

Inlet invert height: 1,220 mm

+ Brochure

Contact us today for a free quote!

CERTIFICATIONS

Tricel septic tanks are fully tested and accredited to European standards for CE certification. The products meets with EN12566-1 requirements which test both the quality of the components as well as the overall performance of the tank.





REQUEST A QUOTE

Ask for a free quote today by clicking the link below

Quote request

CONSULT THE BROCHURE


Learn more about the Tricel Vento

Brochure (/ sewage-treatment/wp-content/uploads/2023/04/Brochure-Tricel-Vento-Septic-Tank.pdf)

INTERACT WITH THE TRICEL VENTO SEPTIC TANK









How to interact with the tank

- Click on the numbers to see the annotations.
- You can also switch between the **treatment process stages** (yellow circle at the bottom left-hand corner) and the **anatomy of the Novo** (green circle at the bottom left-hand corner).
- To view in **Virtual Reality (VR)**, click the square at the top right-hand corner and simply scan the QR code with your phone.
- In order to check the dimensions, click on the spanner icon.
- To download an image of the Novo, click on the camera icon (top right-hand corner)

ACCESSORIES FOR THE TRICEL VENTO

RISERS

If deeper invert levels are necessary, risers are available for deeper installation requirements and are sold separately.

When rises are in use, they are required on both the inlet and outlet sides of the Vento septic tank.

Each riser is 180mm high and can be used to a maximum height of three risers (540mm high).



Buy now (https://septicsdirect.co.uk/riser-extension-for-p6-super-low-pro-septic-tank.htm l)

A distribution box is available to help distribute effluent evenly into individual discharge point.

It is constructed from durable thermoplastic material. Lid included.

Dimensions (LxWxH) 350x350x450mm

Manhole Diameter 300mm

Li	ightweight and easy to handle
	Tricel Vento with risers

Extensive industry experience, manufacturing since 1973.

Tricel manufacture deliver & install water tanks and sewage treatment plants across a wide range of industry sectors throughout Ireland & the UK. Tricel also provide import/export services for our international clients. Top quality material offers outstanding capabilities including long life, durability and is a cost-effective solution for sewage treatment even in the harshest environments.

Tricel has installed many of its Tricel Vento septic tanks accross the UK.

Check some of our projects by clicking on the button below.

Consult our case studies (/sewage-treatment/case-studies/)

50 YEARS IN BUSINESS

A highly successful multinational corporation with over 50 years' valuable industry experience

Δ

SEWAGE TREATMENT PLANTS

Plants available for all capacities, from 1PE up to 50PE. Free advice on request.

攉

FAST DELIVERY

On-time delivery is a core requirement of our successful business operations

FREQUENTLY ASKED QUESTIONS

MY SEPTIC TANK NEEDS TO BE REPLACED TO COMPLY WITH THE NEW REGULATIONS... WHAT SHOULD I DO?

WHAT ARE THE SEPTIC TANK OPTIONS FOR HOMEOWNERS AND SMALL BUSINESSES?

HOW MUCH DOES A SEPTIC TANK COST?



GET IN TOUCH

First name*	
Last name*	
Email*	
Phone number*	
United Kingdom ▼ +44	
Postcode*	
Type of Request*	
Please Select	▼
Type of Product	
Please Select	▼
Are you a?*	
Please Select	▼
Your Enquiry is for*	
Please Select	▼

How many bedrooms?	
Where did you hear about Tricel?	
Diama Calast	
Please Select	▼
Message*	

From time to time, Tricel would like to contact you via email about product and regulation updates.

O I agree to receive other communications from Tricel (https://tricel.co.uk/sewage-treatment/privacy-policy/).

Tricel is committed to protecting and respecting your privacy.

By submitting this form, I accept the <u>privacy policy</u> (https://tricel.co.uk/sewage-treatment/privacy-policy/) and I agree that the information entered may be used for the purposes of the contact request and the commercial relationship that may result from it / to contact me again.

SUBMIT

TRICEL GROUP

TRICEL IS ONE OF EUROPE'S LARGEST MANUFACTURERS OF SEWAGE TREATMENT PLANTS AND IS REGARDED BY REGULATORS AS STANDARD-SETTERS WITHIN THE INDUSTRY.

AS EXPERTS IN SHEET MOULDING COMPOUND (SMC), TRICEL DESIGN, DEVELOP AND SUPPLY WASTEWATER TREATMENT PLANTS CONSTRUCTED FROM THIS VERSATILE MATERIAL. THE PROCESS PRODUCES THE HIGHEST STRENGTH-TO-THICKNESS RATIO OF ANY TANK AVAILABLE ON THE MARKET. IT HAS THE ADDED BENEFIT OF NO RISK OF CORROSION OVER TIME.

OUR COMPANY PROVIDES INDUSTRY-LEADING INNOVATIVE SOLUTIONS THAT OUR CUSTOMERS CAN TRUST. WITH OPERATIONS IN 12 LOCATIONS ACROSS EUROPE, WE SUPPLY A COMPREHENSIVE RANGE OF PRODUCTS TO OVER 50 COUNTRIES WORLDWIDE.

Copyright © 2024 - Tricel Killarney Ltd



```
р
               S:
              //
               W
               W
ht
       ht
              W.
t
        t
               У
р
       р
               0
S:
       S:
              ut
//
       //
               u
W
       W
               b
W
       W
               e.
W.
       W.
               C
fa
       Ιi
               0
С
       n
              m
е
        k
b
       е
               С
       di
0
               h
       n.
0
               а
k.
       С
               n
С
       0
0
       m
       /
m
/ T
       C
ri
       0
C
       m
              1H
el
       р
               Cl
Ε
       а
(https://www.speqifiedby.com/tricel-environmental-uk)
Vİ
FRODUCT RANGE D
SEWAGE TREATMENT/ SEWAGE- TREATMENT/ SEWAGE- TREATMENT- PLANTS/)
                  TREATMENT (/ SEWAGE- TREATMENT/ COMMERCIAL - PLANT- TRICEL - MAXUS-
SEWAGE-TREATMENS-PLANT/)
APTIC TANKS (/ SEXAGE- TREATMENT/ SEPTIC- TANKS/)
                               TREATMENT/PURAFLO-PACKAGED-FILTER-SYSTEMS/)
        6
PUMPING STATIONS SEWAGE-TREATMENT/PACKAGED-PUMPING-SYSTEMS/).
               0
ONLINE STORE (HTTPS://SEPTICSDIRECT.CO.UK/)
               Ε
               0
               R
               W
```

(111145.//111001.00/):

 $_g = 1\%2 Azy 6 uwm\ \%2 A_g a\ \%2 AODg z OTkxOTk 4 LjE2ODE5\ OTgwNjY.\%2 A_g a_RB3VSBTV30\%2 AMTc\ wMDlxNzE0My4xMTQuBARAN AMTQUBARAN

Tricel EU Group Website (https://tricel.eu/? _gl= 1%2Azy6uwm %2A_ga%2AODgzOTkxOTk4LjE20DE5OTgwNjY.%2A_ga_RB3VSBTV30%2AMTcwMDlxNzE0My4xMTQ

Privacy Policy (/s ewa ge- treatm ent/privacy-policy/)

Terms and Conditions (/s ewa ge-treatm ent/terms-and-conditions/)

Cookie Policy (/s ewa ge-treatm ent/cookie-policy/)

Susta in a bility (/s ewa ge-treatment/susta in a bility/)

Visit Tricel EU for: News (https://tricel.eu/n ews/) History (https://tricel.eu/tricel-history/)