



Water Use Assessment

Calculation Report

Certificate Ref: BE45259888 Performance Target: 110 (litres / person / day)

Issued: 01 November 2023 Building Regulations Part G - 110l

Flat 1A - 12 Lind Road Number of Bedrooms: 1

David Barnard Occupancy for Calculation Purposes 2

Installation Type	Unit	Capacity/ Flow Rate	Use Factor	Fixed use (I/p/day)	Total Use (I/p/day)
WC's	Volume (I)	3.50	4.42	0.00	15.47
Taps Exc. Kitchen	Flow Rate	5.00	1.58	1.58	9.48
Baths	(I)	180.00	0.11	0.00	19.80
Showers	(I/s)	8.00	4.37	0.00	34.96
Kitchen Taps	(I/s)	8.00	0.44	10.36	13.88
Washing Machines	(I/kgdry)	8.17	2.10	0.00	17.16
Dishwashers	(l/place)	1.25	3.60	0.00	4.50
Waste Disposal	(I/s)				0.00
Water Softener	(I/s)				0.00
Total Calculated Water Use (I/p/day)					115.25
Grey/Rainwater Reused (I)					0.00
Normalisation Factor					0.91
Total Water Consumption (I/p/day)					104.88
External Water Use Allowance (I)					5.00
Total Consumption Part G (I/p/day)					109.88
Part G Reg Assessment Result					Pass √

The calculation methodology uses the water consumption figures provided from manufacturers' product details. Where details have not been provided, assumed figures have been used to achieve compliance. These must be met in order to satisfy the Part G Calculation for Flat 1A - 12 Lind Road. The calculation methodology is to be used to assess compliance against the water performance targets in Regulation 36. It is not a design tool for water supply and drainage systems. It is also not capable of calculating the actual potable water consumption of a new dwelling. Behaviour and changing behaviour can also have an effect on the amount of potable water used throughout a home.



Appliance/Usage Details

F F											
Taps (Excluding Kitchen	Гарѕ)			Showers							
Tap Fitting Type	Flow Rate	Quantity	Total per	Shower fitting	Flow Rate	Quantity	Total per				
, ,,,	Litres/Min	(No.)	Fitting type	Type	Litres/Min	(No.)	Fitting type				
Bathroom sink mixer taps	5	1	5.00	Shower	8	1	8.00				
T-1-1N1 ([:11: (N1-)			1	T-1-1N1 (T:11: /N1-)			4				
Total No. of Fittings (No.) Total Flow (I/s)			5.00	Total No. of Fittings (No.) Total Flow (I/s)			8.00				
Maximum Flow (I/s)			5.00	Maximum Flow (I/s)			8.00				
Average Flow (I/s)			5.00	Average Flow (I/s)			8.00				
Weighted Average Flow (I/s)		3.50	Weighted Average Flow (I/	/s)		5.60				
Flow for Calculation (I/s)	1, 3,		5.00	Flow for Calculation (I/s)		8.00					
			0.00				0.00				
Baths				WCs							
Bath Type	Capacity to	Quantity	Total per		Full Flush	Part Flush	Quantity (No)				
	Overflow	(No.)	Fitting type	WC Type	Volume	Volume					
Bath	180	1	180.00	Dual flush toilet	4.5	3	1				
Total Nic. of Fittings (Nic.)			1								
Total No. of Fittings (No.)			180.00	Total number of fittings			1				
Total Capacity (I) Maximum Capacity (I)			180.00	Average effective flushing	3.50						
Average Capacity (I)			180.00	7 Verage effective flushing volume 0.30							
Weighted Average Capac	ity (I)		126.00								
Capacity for Calculation (180.00								
Dishwashers	. 5		-	Washing Machines							
Dishwasher Type	L per Place	Quantity	Total per	Washing Machine	L per Kg	Quantity	Total per				
Distance	Setting	(No.)	Fitting type	Type	Dry Load	(No.)	Fitting type				
Dishwasher	1.25		1.25	Washing Machine	8.17	1	8.17				
Total No. of Fittings (No.)			1	Total No. of Fittings (No.)			1				
Total Consumption (I)			1.25	Total Consumption (I)			8.17				
Maximum Consumption (1)		1.25	Maximum Consumption (I)			8.17				
Average Consumption (I/s			1.25	Average Consumption (I/s)			8.17				
Weighted Average Consu			0.88	Weighted Average Consur			5.72				
Consumption for Calculat			1.25	Consumption for Calculation (I/s) 8.17							
Kitchen Taps				Other Fittings							
Tap Fitting Type	Flow Rate	Quantity	Total per	Waste Disposal Y/N		N					
IZU ala ara Tara	Litres/Min	(No.)	Fitting type	Water softener	/ - / -l						
Kitchen Tap	8	1	8.00	Consumption beyond 4% I	/p/a						
				Use of grey water and harvested rainwater							
Total No. of Fittings (No.)			1	Ose of grey water and har	vesteuraniw	ater					
Total Flow (I/s)			8.00	Total Grey water from WH	IR tans (I)						
Maximum Flow (I/s)			8.00	Total Available Grey Water Supply (I)							
Average Flow (I/s)			8.00	Possible Demand (I)							
Weighted Average Flow (l/s)		5.60	Grey/Rain Installed Capacity (I)							
Flow for Calculation (I/s)	•		8.00	Figure for Calculation lit/person/day							
					, [•				