

## **REHAU TOTAL70c Casement Window (Chamfered)**

- Larger reinforcement chambers allow for additional strength / rigidity when necessary
- Optional features include a part sculptured T Sash 3 Ideal replacement for British timber Casement
- Windows due to 70mm depth
- 4 4mm to 44mm double or triple glazing S Wide range of styles and combinations eg. French,
- Bay and Bow windows
- Can achieve U-Values of 0.8 W/m<sup>2</sup>K using the triple glazed Argon sealed units.
- Complies with Building Regulations

Feature	Specification	
Profile depth	70mm	
Maximum window size	900 x 1500mm (Side Hung)	
0	1300 x 1000 (Top Hung)	
Thermal performance	Can achieve 0.8 W/m²K	
Maximum sash weight	40kg	
Glass width	4 – 44mm	
Accreditations	See page 60	



Window Replacement -

REHAU TOTAL70c Top Hung Casement Window (Chamfered), White Coloured

0	1	
		I

2

## NOTES:

This drawing is the copyright of John Verkaik and should not be copied without cons

All work must be carried out in accordance with the requirements of the current British Standards and Building Regulations.

The contractor must verify all levels and dimensions on site before commencing any work or preparing shop drawings. Any discrepancies should be notified to the architect mmediately

Use written dimensions only. Do not scale off this drawing. If in doubt please ask.

No. Revision Description

Checked

Date



JV Architects Broadfield Road Folkestone Kent CT20 2JT Email: john@jv-architects.co.uk Mob: 0787 635 3484

PROJECT NO. 2407

CLIENT/PROJECT MRS HELEN SIST 19B TEMPLAR STREET, DOVER, KENT. CT17 **OBP** 

DRAWING TITLE

PROPOSED FRONT ELEVATION

SCALE 1:50 AT A3

STATUS

PLANNING

3

DRAWN BY

CHECKED JV

SW DRAWING NO.

APRIL 2024 REV NO.

AREA

DATE

2407-PL-03