

Notes

- DO NOT SCALE -

NOIGS

- 1. All works to be carried out in accordance with:
- 1.1 Design and Construction Guidance (DCG) and Sewerage Sector Guidance (SSG) for all sewers proposed to be offered for adoption. (note - the SSG replaces Sewers for Adoption (SfA) for all new developments)
- 1.2 BS EN 752 'Drain and Sewer Systems Outside Buildings'
- 1.3 Current applicable Building Regulations
- 1.4 BGP Specifications
- 1.5 Manufacturer installation guidance and requirements
- 2. All levels shown are in metres and are relative to ordnance datum (m AOD).
- Connection to Northumbrian Water sewers are only to be carried out under an S106 agreement by NWL approved term contractors unless agreed otherwise between both parties. (organised by main contractor)
- Invert levels of all existing chambers and connection points are to be confirmed and engineer advised prior to commencement of any Drainage Works.
- Where proposed sewers connect into existing sewers, the existing sewers must to be checked for line, level and condition preferably by a CCTV survey
- Concrete bed and surround is required to all gully leads and to all pipes in highways/hardstanding where cover to pipe <1200mm
- All pipes to be either extra strength V.C. to BS 65 or PVC certified to WIS 4-35-01 and BS/EN13476 or concrete pipes Class 120 to BS/EN 1916/BS5911-1 2002.
- All RWP and slab penetration locations are indicative and accurate positions should be taken from the Architects drawings. All slab penetrations to be roddable above ground level via access pipe
- Existing sewer positions are indicative and are not to be used in conjunction with design. Contractor to confirm location.
- 10. All existing drainage to be cleaned and jetted as part of the contract
- 11. All RWP connections to be 100Ø and Surface water sewers to be 150Ø unless noted otherwise.
- 12. All FW drains to be 150Ø UNO unless noted otherwise.
- Contractor is responsible for positioning MHs so they do not compromise line or level of kerbing or other delineation at the juncture of two surface materials.
- 14. Cover levels shown are indicative and may vary on site. The contractor should adjust levels to suit site conditions
- 15. All internal manholes to be Type Y with double seal covers u.n.o
- 16. An underground attenuation tank is to be provided which has a capacity of 450m³. Tanks shall be designed by specialist contractor to provide the net volume of attenuation required and comply with recommendations by Ciria with regard to access for maintenance and strength. The strength of the tank should comply with Ciria document C737" Structural design of Modular Geocell drainage tanks". The construction, installation and venting requirements of the tank shall be strictly in accordance with manufacturer guidance.
- Other services are not shown on this drawing, however their presence must be anticipated. The contractor is to confirm prior to commencing any works, the location and depth of all services that may affect the works the manufacturers requirements and recommendations.
 S.H.E.

Do not excavate until all underground services have been identified and marked out. Refer to service providers drawings and to the utilities survey drawings. Unknown underground services may exist. Check for services by carrying out a scan with a cable avoidance tool.

		Legend							
		Proposed SV	V Drain			_			
		Proposed FV	V Drain				r (—	
		Existing FW	Drain	<u> </u>	· ·				
		Existing SW	Drain						
		Site Bounda	ry						
		PPIC MH / S	ilt Trap						
		PCC MH							
		Proposed Pe	ermeable Paving						
		Perforated C	ollector Pipe						
							٦		
					R PRIC	NG			
		1						7	
****		l	NOTE		DNSTRL		ION		
		Issued for P	lanning		ZW F	201 F	RJW 1	9.04.2024	
and the set of the set of the set of		AMENDME			BY REV CHK DATE				
					ດດ				
			Billingh	urst G	eorge &	Pa	rtner	S	
			•		NEERS BUILD				
			У @ВС	Pconsulting	www.bgp-consulti	ng.co.uk			
			Teesside	01642 876470	Tyneside 0191	495 4100)		
		Client	The Ed	ucation	Training C	ollec	tive		
and risk		Project NETA Relocation - Stockton Riverside College							
		BGP Project No. 226254							
narge to utfalls		Drawing Title	e Draina	ge GA -	Overall				
		Drawn ZW	Date 19.04.24	Checked RJW	Date 19.04.24	Size A 1	Scale 1:400	rev . P01	
d Local ing.		Location 226254	originator BGP	Volume	Level ZZ	Form D	Role C	Unique No . 01130	
bosed	_	File Reference							
JUSEU		la instance - · ·			-ZZ-D-C-(equals and the state	
		in instances whe	re this drawing complete	es or partiy comple	nes a contract, Billinghu		& Partners will t advises to th	consider that it's	