

CONC. ROOF TILES TO MATCH EXISTING ON TREATED 38x25mm BATTENS ON TYVEC OR SIMILAR ROOFING FELT.  
 150x50mm SOFT WOOD ROOF TIMBERS AT 450mm CENTRES.  
 250x32mm FASLIA

CODE 4 LEAD FLASHING BUILT INTO EXISTING WALL & DRESSED OVER ROOF TILES.

INSULATION BETWEEN CEILING JOISTS & OVER JOISTS, 300mm THICK.

125x50mm JOISTS

100x75mm PLATE

175x50mm TIMBER BOLTED TO EXISTING WALL. JOIST HANGERS AT 450mm CENTRES.

18mm PLASTERBOARD CEILING  
 12mm " ON WALLS  
 SET COAT PLASTER.

102mm FACE BRICK

100mm CAVITY INSULATION

100mm THERMALITE OR SIMILAR BLOCKS

DPC

150mm G.L.

75mm SCREED

150mm INSULATION

GOOD FORTHING D.P.M.

100mm CONCRETE

150mm HARD CORE WELL CONSOLIDATED

150x50mm TIMBER BOLTED TO EXISTING WALL.

2 NO 175x50mm TRIMMERS TO EXISTING JOISTS WITH JOIST HANGERS

220

2330

20mm CHIPBOARD FLOORING

EX. 150x50mm JOISTS WITH 150mm INSULATION BETWEEN

EXISTING GARAGE CONC. FLOOR

2 COATS SYNTHA PROOF OR SIMILAR DAMP PROOFING



SECTION

SCALE 1:20

2 ASD-17 DF/H

500

1.0M.