



# WL95

IP65 CCT & wattage switchable bulkhead with white housing & conduit entries

## Features

IK rating	IK10
IP rating	IP65
CSP Switchable	Colour switchable
Sensor Option	Microwave (Step-Dim)
Dimmable Option	No
LED Lifetime	35,000h L70
CRI	80 Ra
Emergency Option	Yes

## Installation information

Install Connector Type	4 ways, push-fit
UK Bathroom Zone	2
Inrush Current	10A 50s
Construction Material	ABS housing PC diffuser
Weight	850g
Maximum Ambient Temperature	-20° to 40°C
Electric Class (1, 2, 3)	2

## Wiring information

Cable / Flying Lead	Push-fit terminals, 1.5mm <sup>2</sup> max, loop-in/loop-out.
Type of Wiring Required	Parallel

## Accessories

WL95BEW	White Eyelid Accessory	Sold Separately
---------	------------------------	-----------------



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

3 years

## Features & benefits

CCT switchable between 3000K, 4000K & 6500K

Wattage switchable between 10W & 15W

Emergency option available

Slimline design

Multiple mounting options: BESA box, M20 conduit, cable glands

IP65 rated, making it perfect for using outdoors

High efficacy of 120lm/W

Multiple black bezel options available



Easy access push fit screwless terminals

Microwave step-dim dusk-dawn sensor, which is programmable by dip switches, saving energy by having it on only when needed

Light source energy efficiency:



Beam angle: 115°






collingwood

## Photometrics @ 25°C

Product code	Finish	Feature l	W	Colour	Beam	lm	lm/W	lx @ 1m	EM
WL9515SCS	White	Standard	10W	3000K	115°	1100	110	364	-
WL9515SCS	White	Standard	10W	4000K	115°	1200	120	397	-
WL9515SCS	White	Standard	10W	6500K	115°	1200	120	397	-
WL9515SCS	White	Standard	15W	3000K	115°	1650	110	546	-
WL9515SCS	White	Standard	15W	4000K	115°	1800	120	596	-
WL9515SCS	White	Standard	15W	6500K	115°	1800	120	596	-
WL9515MCS	White	Microwave Sensor	10W	3000K	115°	1100	110	364	-
WL9515MCS	White	Microwave Sensor	10W	4000K	115°	1200	120	397	-
WL9515MCS	White	Microwave Sensor	10W	6500K	115°	1200	120	397	-
WL9515MCS	White	Microwave Sensor	15W	3000K	115°	1650	110	546	-
WL9515MCS	White	Microwave Sensor	15W	4000K	115°	1800	120	596	-
WL9515MCS	White	Microwave Sensor	15W	6500K	115°	1800	120	596	-
WL9515ECS	White	Emergency	10W	3000K	115°	1100	110	364	120
WL9515ECS	White	Emergency	10W	4000K	115°	1200	120	397	120
WL9515ECS	White	Emergency	10W	6500K	115°	1200	120	397	120
WL9515ECS	White	Emergency	15W	3000K	115°	1650	110	546	120
WL9515ECS	White	Emergency	15W	4000K	115°	1800	120	596	120
WL9515ECS	White	Emergency	15W	6500K	115°	1800	120	596	120
WL9515CCS	White	Microwave and Emergency	10W	3000K	115°	1100	110	364	120
WL9515CCS	White	Microwave and Emergency	10W	4000K	115°	1200	120	397	120
WL9515CCS	White	Microwave and Emergency	10W	6500K	115°	1200	120	397	120
WL9515CCS	White	Microwave and Emergency	15W	3000K	115°	1650	110	546	120
WL9515CCS	White	Microwave and Emergency	15W	4000K	115°	1800	120	596	120
WL9515CCS	White	Microwave and Emergency	15W	6500K	115°	1800	120	596	120
WL9515SCSB	Black	Standard	10W	3000K	115°	1100	110	364	-
WL9515SCSB	Black	Standard	10W	4000K	115°	1200	120	397	-
WL9515SCSB	Black	Standard	10W	6500K	115°	1200	120	397	-
WL9515SCSB	Black	Standard	15W	3000K	115°	1650	110	546	-
WL9515SCSB	Black	Standard	15W	4000K	115°	1800	120	596	-
WL9515SCSB	Black	Standard	15W	6500K	115°	1800	120	596	-
WL9515ECSB	Black	Emergency	10W	3000K	115°	1100	110	364	120
WL9515ECSB	Black	Emergency	10W	4000K	115°	1200	120	397	120
WL9515ECSB	Black	Emergency	10W	6500K	115°	1200	120	397	120
WL9515ECSB	Black	Emergency	15W	3000K	115°	1650	110	546	120
WL9515ECSB	Black	Emergency	15W	4000K	115°	1800	120	596	120
WL9515ECSB	Black	Emergency	15W	6500K	115°	1800	120	596	120
WL9515MCSB	Black	Microwave Sensor	10W	3000K	115°	1100	110	364	-
WL9515MCSB	Black	Microwave Sensor	10W	4000K	115°	1200	120	397	-
WL9515MCSB	Black	Microwave Sensor	10W	6500K	115°	1200	120	397	-
WL9515MCSB	Black	Microwave Sensor	15W	3000K	115°	1650	110	546	-

01604 495 151  
collingwoodlighting.com

 collingwoodled

 /collingwoodlighting

 collingwoodlighting

## WL95

Bulkheads are a simple yet functional product that offer a practical solution for lighting commercial spaces, corridors and stairways, as well as indoor and outdoor communal spaces. With a high efficacy and a choice of two lumen levels, this easy install, colour switchable light is a robust and durable option.